


# Unit Bearing Fan Motors

## Features:

- Aluminum & Cast Iron
- All Models Include Vibration Dampening Hub Washer, Speed Nut and 4 Mounting Screw
- Continuous Duty, Air Over
- 60/50 Hz
- Shaded Pole
- 115 & 230 Volt
- Totally Enclosed
- UL & CSA Recognized
- Horizontal and shaft up mounting only



## CAST IRON - TWO MOUNTING FEET

Watts Output	RPM	Volts	Amps	Stock Number	Rotation	Rear Mounting Holes	"A" Dim.	Emerson Number	Notes
2	1550	115	0.22	UB02CWL2F	CWLE	3	2.52		
4	1550	115	0.29	UB04CWL2F	CWLE	3	2.52	2115	
4	1550	115	0.29	UB04CCL2F	CCWLE	3	2.52	2103	
4	1550	230	0.15	UB04CWH2F	CWLE	3	2.52	2123	
4	1550	230	0.15	UB04CCH2F	CCWLE	3	2.52	2122	
5	1550	115	0.34	UB05CWL2F	CWLE	3	2.52	2119	
6	1550	115	0.40	UB06CWL2F	CWLE	3	2.74	2117	
6	1550	115	0.36	UB06CCL2F	CCWLE	3	2.74	2116	
9	1550	115	0.55	UB09CWL2F	CWLE	3	2.74	2108	
9	1550	115	0.55	UB09CCL2F	CCWLE	3	2.74	2118	
9	1550	230	0.27	UB09CWH2F	CWLE	3	2.74	2110	
9	1550	230	0.27	UB09CCH2F	CCWLE	3	2.74	2109	
16	1550	115	1.0	UB16CWL12F	CWLE	3	3.11	2112	
16	1550	115	1.0	UB16CCL12F	CCWLE	3	3.11	2111	
16	1550	230	0.50	UB16CWHV12F	CWLE	3	3.11	2114	
16	1550	230	0.50	UB16CCHV12F	CCWLE	3	3.11	2113	

## ALUMINUM - TWO MOUNTING FEET

Watts Output	RPM	Volts	Amps	Stock Number	Rotation	Rear Mounting Holes	"A" Dim.	Emerson Number	Notes
4	1550	115	0.29	UB04CWL2F	CWLE	5	2.25	D554	
4	1550	115	0.29	UB04CCL2F	CCWLE	5	2.25	D555	
5	1550	115	0.34	UB05CWL2F	CWLE	5	2.25	D582	
5	1550	115	0.34	UB05CCL2F	CCWLE	5	2.25	D583	
6	1550	115	0.40	UB06CWL2F	CWLE	5	2.50	D558	
6	1550	115	0.40	UB06CCL2F	CCWLE	5	2.50	D559	
9	1550	115	0.50	UB09CWL2F	CWLE	5	2.50	D562	
9	1550	115	0.50	UB09CCL2F	CCWLE	5	2.50	D563	
9	1550	230	0.25	UB09CWH2F	CWLE	5	2.50	D564	
9	1550	230	0.25	UB09CCH2F	CCWLE	5	2.50	D565	

### Notes:

See Parts & Accessories starting on page 258

## Energy Savings ECM Motor

Manufactured by Electric Motors & Specialties



### Features:

- Advanced ECM Design
  - Up to 65% Efficiency
  - Rain Shielded
  - Cast Iron
  - 13" Leads
  - Lvall Plug
  - UL Approved E128044
  - Wide temperature range oil for use in evaporators and condensers.
  - Tapped & Drilled Mounting Holes
- Evaporator Mount - Standard 3-hole, 4-hole Hussmann Style  
Condenser Mount - Double boss

iMotor®

Breakthrough motor design offers huge energy savings for the refrigeration market.

Replaces 6, 9, 12 and 14, 15, 16 watt PSC and low efficiency shaded pole motors in evaporators and condenser units.

Direct Drop-in Replacement for supermarket case evaporator fans and condenser units



Watts	RPM	Volts	Amps	Stock No.	ROT OSE	Rear Mounting Holes	"A" Dim.	Notes
6, 9, 12	1550	115	.2-.3	9207F2	CW	5	2.93	New!
14, 15, 16	1550	115	.47-.58	9208F2	CW	5	2.93	New!