

Century® Farm Building Direct Drive Fan Motors

Features:

- Auto Protector
- Class B Insulation
- Direct Drive
- Double Sealed Ball B bearings
- Extended 10-32 Thru-bolts 3/4" Past Nut
- Fully Gasketed
- Reversible
- Service Factor 1.0
- Single Phase
- 60 Hz
- 40°C Ambient
- Totally Enclosed, Air Over



Applications: Designed for farm air movement applications.

HP	RPM	Speeds	Volts	Full Load Amps	Frame	Stock Number	Shaft	"C" Dim.	Notes
RESILIENT BASE									
1/4	1700	1	115/230	3.4/1.7	48Z	C042A	1/2 x 3-1/8	10.1	70,132,133
1/4	1100	1	115/230	4.0/2.0	48Z	C045A	1/2 x 3-1/4	9.3	70,132,133
1/4	1100	2	115	3.4	48Z	C059A	1/2 x 3	10.1	70
1/3	1725	1	115/230	3.6/1.8	48Z	C043A	1/2 x 3-1/8	10.1	70,132,133
1/3	1100	1	115/230	4.2/2.3	48Z	C046A	1/2 x 3-1/4	10.0	70,132,133
1/2	1700	1	115/230	5.5/2.8	48Z	C044A	1/2 x 3	11.0	70,132,133
1/2	1100	1	115/230	6.5/3.25	48Z	C047A	1/2 x 3-1/8	11.1	70,132,133
1/2	900	1	115/230	7.1/3.6	48Z	C039A	1/2 x 2-1/2	11.0	70,132,133
1/2	900	1	115/230	6.6/3.3	56Z	C048	5/8 x 2-1/2	12.1	70,134
THRU BOLT MOUNT (10-32 UNF-2A)									
1/3	1800	1	115	4.8	56Z	F683	1/2 x 2	11.12	62
1/3	1800/900	2	115	5.5/3.1	56Y	F684	1/2 x 2	11.12	62
1/3	1200	1	115	4.7	48Z	971	1/2 x 2	6.80	1,3,70,146,228
RIGID BASE									
1	900	1	230	5.1	56CZ	C783	5/8 x 3-1/4	14.22	6,44,70

Notes:

- Item to be discontinued when stock is depleted
- Special OEM replacement motor
- 60/50 Hertz
- CCWLE rotation only
- Split Phase
- Permanent Split Capacitor
- Shaft sleeve and key supplied for 5/8" diameter
- Shaft N-W = 2.50" with two flats .04 deep, 2.16" long, 90° apart
- Shaft N-W = 2.50" with 5/8" diameter and keyway
- No base
- CWSE not reversible

