

Shaded Pole and Permanent Split Capacitor Ventilation Direct Drive Blower 5.0" and 5.6" Diameter, Open Air Over




APPLICATIONS:

To meet manufacturer's requirements for direct drive ventilation units.

FEATURES:

- Capacitor Included and Mounted on PSC Models
- Automatic Reset Thermal Overload Protector
- Continuous Duty
- Ball Bearings Unless Noted
- 40°C Ambient
- 1.0 Service Factor
- **Discount Symbol: DS-3HAC**



HP	RPM	Voltage	Catalog Number	List	NEMA [†] Frame	Amps	Motor Type	Shaft N	Shaft U	Rotation Lead End	Length XI	Total C	Ship Wt. (lbs)	Notes
1/12	850	115	4740	\$143	48YZ	1.7	PSC	3.25	0.500	CW	5.81	9.06	10	
1/6	1650	115	4742	\$122	42YZ	2.7	PSC	3.25	0.500	CW	5.81	9.06	10	
	1100	115	1146	\$170	48YZ	2.2	PSC	3.00	0.500	CCW Rev	3.81	7.36	10	
1/3	1650	115	4745	\$167	48YZ	4.0	PSC	3.25	0.500	CW	6.06	9.31	14	
	1100	115	4746	\$176	48YZ	4.4	PSC	3.25	0.625	CW	5.81	9.06	17	
	1075	115	1145	\$185	48YZ	4.9	PSC	3.00	0.500	CCW Rev	4.81	7.81	15	
1/2	1650	115/230	4748	\$209	48YZ	8.0/4.0	PSC	3.25	0.625	CW	6.31	9.56	18	
	1100	115/230	4749	\$218	48Y	6.2/3.1	PSC	3.30	0.625	CW	6.60	9.90	20	
3/4	1100	115/230	4750	\$235	48YZ	10.0/5.0	PSC	3.25	0.625	CW	6.56	9.81	24	

Permanent Split Capacitor Ventilation Direct Drive Blower 5.6" and 6.3" Diameter, Totally Enclosed Air Over




APPLICATIONS:

To meet manufacturer's requirements for direct drive ventilation units requiring a totally enclosed motor.

FEATURES:

- Continuous Duty
- 1/2" Diameter x 2-1/2" Diameter Shaft
- Reversible Rotation
- Studs For Mounting Fan Guard
- Terminal Board With Side Conduit Plug
- Automatic Thermal Protection
- Includes Capacitor Mounted With Cover
- **Discount Symbol: DS-3HAC**



HP	RPM/ Spds	Voltage	Catalog Number	List	NEMA [†] Frame	Amps	Eff.	SF	Bearings	Insul. Class	Total C	Ship Wt. (lbs)	Notes	OEM
1/4	1020	115	4153	\$224	48Y	4.5	Std	1.00	SAB	B	10.0	8.5		MQ
	1075/2	115	4812	\$227	48Z	3.3	Std	1.00	SAB	A	9.9	18		
	1725	115	6326	\$246	56Z	5.0	Std	1.00	Ball	A	9.8	18	94	
1/3	1075	115	4815	\$208	48Z	4.6	High	1.00	SAB	A	10.5	18		
	1725	115	8511	\$209	48Z	5.2	Std	1.00	Ball	B	10.2	15	94	
1/2	1075	115	4816	\$230	48Z	7	High	1.00	SAB	B	10.9	20		
	1725	115	6330	\$318	56	7.4	Std	1.00	Ball	A	10.3	23	94	
	1700	115/230	1850	\$295	48Y	5.0/2.5	High	1.00	Ball	B	10.9	25		

MQ = McQuay[†]

† All marks shown within this document are properties of their respective owners.