


Permanent Split Capacitor Direct Drive Fan Single Shaft 5.0" Dia., Open, Air Over




APPLICATIONS:

Designed to meet manufacturer's requirements for use on direct drive fan & blowers.

FEATURES:

- Reversible Unless Noted
- Sleeve Bearings Have All Angle Thrust System
- Designed for Use with 370V Capacitors
- Continuous Duty, Air Over
- 24" Line Leads Unless Otherwise Noted
- Automatic Reset Thermal Overload Protector
- Connection and Capacitor Information Furnished in the Nameplate Data
- **Discount Symbol: DS-3HAC**



Permanent Split Capacitor, 5.0" Diameter, Stud or Hub Ring Mount (2.5")

HP	RPM/ Spds.	Volts	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wgt.	Notes
1/10	1625/3	115	8956	\$131	Slv	5.0	1.2	5.3	4.8	4.3	10.7	.75	9	
1/8	1075/3	115	8950	\$163	Slv	5.0		4.0	4.4	3.9	8.9	.75	9	
1/6	1075	115	6479	\$162	Slv	4.0	2.8	4.1	--	3.8	7.9	N/A	-	H11
1/5	1075/3	115	8951	\$149	Slv	5.0	2.7	4.0	5.3	4.8	9.9	.75	11	
	1075/3	203-230	8952	\$206	Slv	5.0	1.6	4.0	5.3	4.9	9.9	N/A	11	
	1075/4	115	1268	\$150	Slv	4.0	3.5	3.5	4.6	4.1	8.7	1	10	98
1/4	1050	115	6480	\$112	Slv	7.5	4.0	5.0	--	4.1	9.1	N/A	-	H11
	1050/3	115	1390	\$160	Slv	7.5	2.8	4.0	4.9	4.3	8.9	1	13	H24
	1050/3	208-230	1391	\$163	Slv	7.5	1.5	4.0	4.9	4.3	8.9	1	13	H24
1/3	1075/3	115	8955	\$136	Slv	15.0	3.8	4.0	5.1	-	10.2	.75	13	

Note 98 Class B Insulation
Note H11 Band Mounting

Note H24 Hub Rings not included