

## C-Face Ventilator Motors

### Features:

- Ball Bearing
- Class B Insulation
- Dripproof
- Split Phase
- Reversible
- No Base
- 1/12 thru 1/2 Hp
- 40°C Ambient
- 60 Hz
- 4, 6, 8 Pole
- 5/8" Dia. Keyed Shaft



F270

**Applications:** Designed for use on commercial and industrial ventilation systems.

HP	RPM	Volts	Full Load Amps	Service Factor	Frame	Stock Number	Overload Protector	"C" Dim.	Shaft Length	Notes
1/12	850	115	2.6	1.40	56CZ	F395	Auto	11.1	2.38	
1/8	1140	115	3.0	1.40	56CZ	F270	Auto	11.3	2.25	
1/6	1140	115	3.6	1.35	56CZ	F271	Auto	11.3	2.25	
1/4	850	115	6.2	1.35	56CZ	F274	Auto	12.4	2.25	
1/4	1140	115	5.0	1.35	56CZ	F273	Auto	11.3	2.25	
1/4	1725	115	5.3	1.35	56CZ	F392	Auto	9.9	2.25	
1/4~1/12	1725/1140	115	5.4/3.2	1.35	56CZ	F393	Auto	11.8	2.25	
1/3	850	115	8.6	1.00	56CZ	F276	Auto	12.9	2.25	
1/3	1725	115	6.8	1.35	56CZ	F394	Auto	10.2	2.25	
1/3~1/11	1725/1140	115	5.0/3.0	1.35	56CZ	F252	None	11.3	2.25	
1/3~1/11	1725/1140	115	5.4/2.3	1.35	56CZ	F262	Auto	11.3	2.25	
1/2~1/7	1725/1140	115	6.8/3.8	1.25	56CZ	F263	Auto	11.6	2.25	

