


Split Phase Belted Fan & Blower

NEMA[®]† 48 Frame, Single & Two Speed




APPLICATIONS:

Designed to meet manufacturer's requirements for belted fans and blowers.

FEATURES:

- Resilient Base
- Class B Insulation Unless Otherwise Noted
- With Threaded Conduit Hole
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- **Discount Symbol: DS-3HAC**



Single Speed, Open Dripproof

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/3	1725	115/208-230	8438	\$301	Ball	48	6.8/3.1-3.4	2.0	.625	Auto	10.2	1.35	17	
1/4	1725	115	8000	\$127	Slv	48	5.3	1.5	.500	Auto	8.9	1.35	13	77, 79
	1725	115	840CV	\$128	Slv	48	4.8	1.6	.500	Auto	9.4	1.35	16	80, 82
	1725	115	2889	\$251	Ball	48	4.4	1.5	.500	Auto	9.9	1.35	21	83, A
	1725	115/208-230	3617	\$151	Ball	48	5.2/2.5-2.6	1.5	.500	Auto	9.4	1.35	17	
	1725	115	8505	\$192	Ball	48	5.0	1.5	.500	Auto	10.7	1.00	17	
	1725	115/208-230	3618	\$136	Ball	48Z	5.2/2.5-2.6	1.875	.500	Auto	9.3	1.35	14	
1/3	1725	115	8100	\$132	Slv	48	6.7	1.5	.500	Auto	9.4	1.35	15	77, 79
	1725	115	841CV	\$133	Slv	48	5.6	1.6	.500	Auto	9.9	1.35	18	80, 82
	1725	115	2888	\$269	Ball	48	5.4	1.5	.500	Auto	9.9	1.35	18	83, A
	1725	115/208-230	3623	\$178	Ball	48	6.6/3.1-3.3	1.9	.500	Auto	10.3	1.35	19	
1/2	1725	115	8200	\$158	Slv	48	8.7	1.5	.500	Auto	10.0	1.25	18	77, 79
	1725	115	1542C	\$168	Slv	48	7.8	1.6	.500	Auto	9.9	1.25	21	80
	1725	115	2887	\$305	Ball	48	7.8	1.5	.500	Auto	9.9	1.25	21	83, A
	1725	115/208-230	3626	\$219	Ball	48	8.6/4.2-4.3	1.9	.500	Auto	10.3	1.25	20	98
	1725	115/208-230	3627	\$219	Ball	48	8.6/4.2-4.3	1.9	.500	Auto	10.3	1.25	20	H32
	1725	115/230	2695	\$323	Ball	48	7.8/3.9	1.5	.500	Auto	10.4	1.25	20	

Two Speed, Open Dripproof

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/3-1/6	1725/1140	115	1786	\$389	Slv	48	5.8	1.5	.500	Auto	10.4	1.35	22	A
	1725/1140	230	1789	\$404	Slv	48	2.9	1.6	.500	Auto	10.4	1.35	22	A

Note 77 With Shaft Adapter For 5/8" Shaft.
 Note 79 Combination Mounting Holes For NEMA[®]† 48 & 56 Frame Dimensions
 Note 80 Canadian Standard — Connected CCWLE (Reversible)
 Note 82 Open, Ventilated

Note 83 Enclosed Shell, Ventilation Through End Shields By Internal Fan
 Note 98 50/60 Hz
 Note A Class A Insulation
 Note H32 Keyed Shaft

† All marks shown within this document are properties of their respective owners