

# Shaded Pole & Permanent Split Capacitor Unit Heater Fan 5.0", 5.6" & 6.3" Diameter, Totally Enclosed, Air Over



## APPLICATIONS:

Designed to meet manufacturer's requirements for use on unit heaters.

## FEATURES:

- Continuous Duty, Air Over
- Reversible Motors Are Easily Reversed With Quick Connects
- 2-1/2" Diameter Hub Rings When Furnished
- Automatic Reset Thermal Overload Protector
- Green Ground Lead
- 48 Frame Has 8-32 NF-2A Thread; 56 Frame Has 10-32 NF-2A Thread
- 370V Capacitor Is Furnished
- Leads Are SJO Cord
- Extended Mounting Studs
- **Discount Symbol: DS-3HAC**




Figure A




Figure B

## Stud Mount, Single Speed (Fig. A)

HP	RPM/Spd.	Volts	Catalog Number	List	Diameter (In.)	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wgt.	Notes
1/6	1075	115	9034	\$205	5.6	4.0	2.6	2.5	4.9	4.3	7.9	0.8	12	
1/4	1075	115	9035	\$223	5.6	5.0	3.6	2.5	5.8	5.1	8.7	0.8	15	
1/3	1075	115	9036	\$227	5.6	4.0	5.1	2.5	5.8	5.1	8.7	0.8	15	

## Stud Mount, Two Speed (Fig. A)

HP	RPM/Spd.	Volts	Catalog Number	List	Diameter (In.)	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wgt.	Notes
1/6	1075/2	115	4856	\$259	5.6	4.0	2.4	5.0	4.6	4.3	10.4	2.5	12	64
1/3	1075/2	115	1052	\$246	5.6	4.0	4.6	5.0	5.4	4.9	10.9	2.5	14	64

## Resilient Base (Fig. B)

HP	RPM/Spd.	Volts	Catalog Number	List	Diameter (In.)	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wgt.	Notes
1/3	1075	230	1048	\$242	5.6	10.0	1.8	2.8	5.9	4.9	8.7	--	17	H14
1/2	1075/2	230	1810	\$404	6.3	10.0	2.5	4.9	7.5	6.3	12.8	2.5	26	
3/4	1075/2	230	1811	\$409	6.3	12.5	3.7	4.9	8.5	7.3	13.8	2.5	34	

Note 64 Capacitor shipped detached

Note H14 Capacitor mounted OSE, 3/8" shaft

