



Specific Purpose Blowers

MARS SERIES **071**

FIG. A
A165



FIG. B
A168



FIG. C
A220

FIG. D
A221




FIG. E
A222



FIG. F
A223



FIG. G
A224



FIG. H
A225

FIG. I
A226




FIG. J
A227



FIG. K
A228



FIG. L
A229



FIG. M
A230



FIG. N
A231



FIG. O
A234



FASCO MODEL#	TYPE	VOLTS	SPD	AMPS	CROSS REF.	FIG	NOTES
A165	PSC	115	1	0.7	York 7062-3958	A	20
A168	PSC	115	1	0.7	York, Excel, Ducane 7062-5019	B	
A220	SP	115	1	1.6	York 7021-5838, 7021-7217, 7021-9054	C	
A221	SP	208-230	1	0.55	York 7021-8318, 7021-6691	D	
A222	SP	115	1	1.05	York 7021-8317, 7021-7481	E	
A223	SP	208-230	1	0.64	York 7021-10096, 7021-9656	F	
A224	SP	115	2	0.8	York 7062-5048, 7062-4743	G	
A225	SP	115	1	2.25	York 7021-11577, 7021-11577S, 7021-11830, 024-34558-000	H	
A226	SP	115	1	1.7	York 7058-0266, 7058-0266S	I	
A227	SP	115	1	0.7	York 7062-4708S, 7062-4708	J	
A228	SP	115	1	2	York 7002-3285, 7002-2941	K	
A229	SP	115	1	1.75	York 7058-0267S, 7058-0267	L	
A230	PSC	115	2	0.8	York 7062-5094S, 7021-5094	M	
A231	SP	115	2	1.3	York 7021-10213	N	
A234	PSC	208-230	1	0.5	York 7062-5155	O	

NOTES: 20: 4M 370V Capacitor included

All Fasco PSC motors use a 5 mfd at 370 VAC run capacitor, MARS # 12005 or equivalent, unless otherwise noted.