

**Features:**

- Advanced ECM Design
- Up to 65% Efficiency
- Rain Shielded
- Cast Iron
- 13" Leads
- Lyall Plug
- UL Approved E128044
- Wide temperature range oil for use in evaporators and condensers.
- Tapped & Drilled Mounting Holes
  - Evaporator Mount - Standard 3-hole, 4-hole Hussmann Style
  - Condenser Mount - Double boss



**Breakthrough motor design offers huge energy savings for the refrigeration market.**

Replaces 6, 9, 12 and 14, 15, 16 watt PSC and low efficiency shaded pole motors in evaporators and condenser units.

**Direct Drop-in Replacement for supermarket case evaporator fans and condenser units**



9207F2,  
9208F2,  
9211



9214L,  
9214H



9209L,  
9210L,  
9209H,  
9210H



9215L,  
9215H,  
9216L,  
9216H



9212,  
9213

Watts	RPM	Volts	Amps	Stock No.	ROT OSE	Mounting Holes	"A" Dim.	Notes
6, 9, 12	1550	115	.2-.3	<b>9207F2</b>	CW	5 rear mounting holes	2.93	
14, 15, 16	1550	115	.47-.58	<b>9208F2</b>	CW	5 rear mounting holes	2.93	
13	1725	115	0.47	<b>9211</b>	CW	5 rear mounting holes	2.93	<b>New!</b>
6,9,12	1550	115	0.31	<b>9212</b>	CW	7 rear mounting holes	3.03	<b>New!</b>
14,15,16	1550	115	0.41	<b>9213</b>	CW	7 rear mounting holes	3.03	<b>New!</b>
HP	RPM	Volts	Amps	Stock No.	ROT OSE	Mounting Holes	"A" Dim.	Notes
1/15, 1/20, 1/25	1550	115	1.3	<b>9214L</b>	Reversible	4 studs each end	3.58	<b>New!</b>
1/15, 1/20, 1/25	1550	208-230	0.63	<b>9214H</b>	Reversible	4 studs each end	3.58	<b>New!</b>
1/15, 1/20, 1/25	1550	115	1.25	<b>9209L</b>	CCW	4 studs SE	3.20	<b>New!</b>
1/15, 1/20, 1/25	1550	115	1.25	<b>9210L</b>	CW	4 studs SE	3.20	<b>New!</b>
1/15, 1/20, 1/25	1550	230	0.77	<b>9209H</b>	CCW	4 studs SE	3.20	<b>New!</b>
1/15, 1/20, 1/25	1550	230	0.77	<b>9210H</b>	CW	4 studs SE	3.20	<b>New!</b>
1/15, 1/20, 1/25	1625	120	1.2	<b>9215L</b>	CCW	4 studs each end	2.85	<b>New!</b>
1/15, 1/20, 1/25	1625	230	0.7	<b>9215H</b>	CCW	4 studs each end	2.85	<b>New!</b>
1/15, 1/20, 1/25	1625	120	1.2	<b>9216L</b>	CW	4 studs each end	2.85	<b>New!</b>
1/15, 1/20, 1/25	1625	230	0.7	<b>9216H</b>	CW	4 studs each end	2.85	<b>New!</b>

Replaces 1/15, 1/20, 1/25 HP PSC and low efficient shaded pole designs.