

Product Selection

QUICKLAG Type BAB
Single-Pole

QUICKLAG Type: BA 10,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number |
|--|--|---|---------------------------------------|---|
| 10 | BAB1010 | BAB2010 | BAB2010H ③ | BAB3010H ③ |
| 15 | BAB1015 ①② | BAB2015 | BAB2015H | BAB3015H |
| 20 | BAB1020 ①② | BAB2020 | BAB2020H | BAB3020H |
| 25 | BAB1025 | BAB2025 | BAB2025H | BAB3025H |
| 30 | BAB1030 | BAB2030 | BAB2030H | BAB3030H |
| 35 | BAB1035 | BAB2035 | BAB2035H | BAB3035H |
| 40 | BAB1040 | BAB2040 | BAB2040H | BAB3040H |
| 45 | BAB1045 | BAB2045 | BAB2045H | BAB3045H |
| 50 | BAB1050 | BAB2050 | BAB2050H | BAB3050H |
| 55 | BAB1055 | BAB2055 | BAB2055H | BAB3055H |
| 60 | BAB1060 | BAB2060 | BAB2060H | BAB3060H |
| 70 | BAB1070 | BAB2070 | BAB2070H | BAB3070H |
| 80 | — | BAB2080 | BAB2080H | BAB3080H |
| 90 | — | BAB2090 | BAB2090H | BAB3090H |
| 100 | BAB1100 | BAB2100 | BAB2100H | BAB3100H |
| 110 | — | BAB2110 | — | — |
| 125 | — | BAB2125 | — | — |

QUICKLAG Type: BA Non-Automatic Switches

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number |
|--|--|---|---------------------------------------|---|
| 50 | BAB1050N | — | BAB2050N | BAB3050N |
| 60 | BAB1060N | — | BAB2060N | BAB3060N |
| 100 | BAB1100N | — | BAB2100N | BAB3100N |

QUICKLAG Type: QBHW 22,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number |
|--|--|---|---------------------------------------|---|
| 15 | QBHW1015 ① | QBHW2015 | QBHW2015H | QBHW3015H |
| 20 | QBHW1020 ① | QBHW2020 | QBHW2020H | QBHW3020H |
| 25 | QBHW1025 | QBHW2025 | QBHW2025H | QBHW3025H |
| 30 | QBHW1030 | QBHW2030 | QBHW2030H | QBHW3030H |
| 35 | QBHW1035 | QBHW2035 | QBHW2035H | QBHW3035H |
| 40 | QBHW1040 | QBHW2040 | QBHW2040H | QBHW3040H |
| 45 | QBHW1045 | QBHW2045 | QBHW2045H | QBHW3045H |
| 50 | QBHW1050 | QBHW2050 | QBHW2050H | QBHW3050H |
| 55 | QBHW1055 | QBHW2055 | QBHW2055H | QBHW3055H |
| 60 | QBHW1060 | QBHW2060 | QBHW2060H | QBHW3060H |
| 70 | QBHW1070 | QBHW2070 | QBHW2070H | QBHW3070H |
| 80 | — | QBHW2080 | QBHW2080H | QBHW3080H |
| 90 | — | QBHW2090 | QBHW2090H | QBHW3090H |
| 100 | — | QBHW2100 | QBHW2100H | QBHW3100H |
| 110 | — | QBHW2110 | — | — |
| 125 | — | QBHW2125 | — | — |

Notes

- ① Switching duty rated for 120 Vac fluorescent light applications.
- ② For special low-magnetic breaker, order **BAB1015L1** or **BAB1020L1**.
- ③ Not UL listed.

QUICKLAG Type: HBAX 42,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number |
|----------------------------------|--|---|---------------------------------------|---|
| 15 | HBAX1015 ① | HBAX2015 | — | HBAX3015H |
| 20 | HBAX1020 ① | HBAX2020 | — | HBAX3020H |
| 25 | HBAX1025 | HBAX2025 | — | HBAX3025H |
| 30 | HBAX1030 | HBAX2030 | — | HBAX3030H |
| 35 | HBAX1035 | HBAX2035 | — | HBAX3035H |
| 40 | HBAX1040 | HBAX2040 | — | HBAX3040H |
| 45 | HBAX1045 | HBAX2045 | — | HBAX3045H |
| 50 | HBAX1050 | HBAX2050 | — | HBAX3050H |
| 55 | HBAX1055 | HBAX2055 | — | HBAX3055H |
| 60 | HBAX1060 | HBAX2060 | — | HBAX3060H |
| 70 | HBAX1070 | HBAX2070 | — | HBAX3070H |
| 80 | — | HBAX2080 | — | HBAX3080H |
| 80 | — | HBAX2080 | — | HBAX3080H |
| 90 | — | HBAX2090 | — | HBAX3090H |
| 100 | — | HBAX2100 | — | HBAX3100H |

QUICKLAG Type: HBAW 65,000A Interrupting Capacity Thermal-Magnetic Breakers

| Continuous Ampere Rating at 40°C | Single-Pole 120/240 Vac Catalog Number | Two-Pole 120/240 Vac Catalog Number | Two-Pole 240 Vac Catalog Number | Three-Pole 240 Vac Catalog Number |
|----------------------------------|--|---|---------------------------------------|---|
| 15 | HBAW1015 ① | HBAW2015 | — | HBAW3015H |
| 20 | HBAW1020 ① | HBAW2020 | — | HBAW3020H |
| 25 | HBAW1025 | HBAW2025 | — | — |
| 30 | HBAW1030 | HBAW2030 | — | — |

Dimensions

Approximate Dimensions in Inches (mm)

Shipping Data

| Number of Poles | Carton Quantity | Approximate Weight Lbs (kg) | Dimensions |
|-----------------|-----------------|-----------------------------|---|
| 1 | 24 | 9.00 (4.1) | 12.50 x 7.50 x 5.00 (317.5 x 190.5 x 127.0) |
| 2 | 12 | 9.00 (4.1) | 12.50 x 7.50 x 5.00 (317.5 x 190.5 x 127.0) |
| 3 | 8 | 9.00 (4.1) | 12.50 x 7.50 x 5.00 (317.5 x 190.5 x 127.0) |

Note

① Switching duty rated for 120 Vac fluorescent light applications.