















One-On-One™ Direct Replacement Motors

	MARS NO.	MFG. NO	HP	VOLTS	RPM/SPEEDS	ROT	AMPS	DIMENSIONS		
								A	B	C
Trane (con't)										
	A368	-	1/20	115	3200/2	CW SE	0.8	-	-	-
	PSC, sleeve bearing									
	Replaces: 7062-3782, D340623P01 									
	A369	-	1/45	208-230	2800/2	CCW SE	0.3	-	-	-
	PSC, ball bearing									
	Replaces: 7062-3915, C663946P01 									
	A370	-	1/100	208-230	2920/2	CCW SE	0.2	-	-	-
	PSC, ball bearing									
	Replaces: 7062-3918, C664099P01 									
	A373	-	1/35	280-230	3000/1	CCW SE	0.6	-	-	-
	Shaded pole, ball bearing									
	Replaces: 7021-9396, C665662P01 									
	D1050	-	1/8	230	1550/1	CW SE	1.1	3.00	3.25	-
	PSC, ball bearing, original motor is SP, D1050 is PSC to provide greater motor efficiency and permit closing of shaft end to prevent moisture from entering motor									
	Replaces: WW94X236SP, WW94X936PSC 									
	D895	-	1/8	208 - 230	1650/1	CW SE	0.8	1.50	-	-
	PSC, sleeve bearing, 4@370V capacitor required (MARS No. 12004)									
	Replaces: 5KCP39BGR426S, MOT 6363 									

ONE-ON-ONE