


# Special Application Agriculture Totally Enclosed Fan Cooled (TEFC) Agri Duty High Torque Single Phase, Capacitor Start



## APPLICATIONS:

For powering agitators, augers, compressors, conveyors, feeders and hay hoists. High torque motors are used on barn cleaners, manure pumps and silo unloaders.

## FEATURES:

- Class F Insulation (140-210 Frame)
- 40°C Ambient, Continuous Duty
- Reversible Rotation
- F1 Assembly
- Steel Frames & Steel Welded Based (140-210 Frame)
- Manual Reset Thermal Overload Protector
- Steel Fan Cover & Conduit Box
- Non-Regreasable Double Shielded Bearings
- Shaft Slinger (140-210 Frame)
- Capacitor Start-Capacitor Run (3-10 HP)
- Low Temperature Grease

## Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/3	1800	115/230	56	FD13CM2P		DS-3FMP	1.15	10.9	23	6.6/3.3	23
1/2	1800	115/230	56	FD12CM2P		DS-3FMP	1.15	11.4	23	9.0/4.5	23
3/4	1800	115/230	56	FD34CM2P		DS-3FMP	1.15	11.9	32	11.4/5.7	23
1	1800	115/230	143T	FD1CM2P14		DS-3F	1.15	12.8	32	15.0/7.5	23
	1800	115/230	56H	FD1CM2PZ		DS-3FMP	1.15	12.9	23	14.0/7.0	23
1 1/2	1800	115/230	145T	FD32CM2P14		DS-3SP	1.15	14.3	43	16.2/8.1	23,CSCR
	1800	115/230	56H	FD32CM2PH		DS-3FMP	1.15	13.3	32	16.2/8.1	23, CSCR
2	1800	115/230	182T	FD2CM2P18		DS-3SP	1.00	15.2	60	23.6/11.8	23
	1800	115/230	56HZ	FD2CM2PHZ		DS-3FMP	1.00	14.3	40	20.0/10.0	23
3	1800	230	184T	FD3CM2K18		DS-3SP	1.00	17.2	74	14.5	23
5	1800	230	184T	FD5CM2K18		DS-3SP	1.00	18.2	125	22.0	23
	1800	230	213T	FD5CM2K21		DS-3SP	1.00	19.6	180	23.0	23
7 1/2	1800	230	215T	FD7CM2K21		DS-3SP	1.00	22.1	147	30.0	23
10	1800	230	215T	FD10CM2K21		DS-3SP	1.00	22.1	180	38.0	23

## C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/3	1800	115/230	56C	FD13CM2PCR		DS-3FMP	1.15	10.9	21	6.6/3.3	23
1/2	1800	115/230	56C	FD12CM2PCR		DS-3FMP	1.15	11.4	32	9.0/4.5	23
3/4	1800	115/230	56C	FD34CM2PCR		DS-3FMP	1.15	11.9	32	11.4/5.7	23
1	1800	115/230	56C	FD1CM2PCR		DS-3FMP	1.15	12.9	44	14.0/7.0	23
1 1/2	1800	115/230	56C	FD32CM2PCR		DS-3FMP	1.15	13.9	44	16.2/8.1	23

Note 23 Manual Reset Thermal Protector Overload  
Note CSCR Capacitor Start/Capacitor Run

† All marks shown within this document are properties of their respective owners.

