

3.3" Diameter



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D200	SP	1/85	115	3000	1	0.6	Open Vent.	CW	SLV	2-3/8 x 1/4 x 3/4	2	A	15,16,17
D201	SP	1/85	115	3000	1	0.6	Open Vent.	CCW	SLV	1/4 x 1-3/8	2 1/4	A	15,16,17
D229	SP	1/100	115	3000	1	0.55	Open Vent.	CCW	SLV	1/4 x 3-1/2	2 1/2	B	15
D230	SP	1/100	115	3000	1	0.55	Open Vent.	CW	SLV	1/4 x 3-1/2	2 1/2	B	15
D202	SP	1/85	115	3000	1	0.6	Open Vent.	CW	SLV	1/4 x 2-1/4	2 3/8	C	15
D228	SP	1/80	115	3000	1	0.8	Open Vent.	CW	SLV	1/4 x 2	2 1/2	D	15
D203	SP	1/40	115	3000	1	1	Open Vent.	CCW	SLV	1/4 x 2-1/4	2 3/4	C	15
D206	SP	1/30	115	3000	1	1.2	Open Vent.	CW	SLV	1/4 x 2-1/4	2 3/4	C	15
D207	SP	1/30	230	3000	1	0.6	Open Vent.	DS	SLV	2-1/4 x 1/4 x 2-1/4	2 3/4	E	15
D210	SP	1/25	115	3000	1	1.3	Open Vent.	CW	SLV	1/4 x 2-1/4	3 1/4	C	15
D216	SP	1/25	230	3000	1	0.65	Open Vent.	CW	SLV	1/4 x 2-1/4	3 1/4	C	15
D213	SP	1/15	115	3000	1	2.1	Open Vent.	DS	SLV	2-3/4 x 1/4 x 2-3/4	3 7/8	F	15
D211	SP	1/15	230	3000	1	1.1	Open Vent.	DS	SLV	2-1/2 x 1/4 x 2-1/2	3 7/8	F	15
D402	SP	1/60	115	3000	1	0.75	Totally Encl.	CW	SLV	1/4 x 1-3/4	2 3/8	G	15
D403	SP	1/60	115	3000	1	0.75	Totally Encl.	CCW	SLV	1/4 x 2-1/4	2 3/8	G	15
D205	SP	1/40-1/70	115	3000	2	1-.5	Totally Encl.	DS	SLV	3 x 1/4 x 3	2 7/8	H	15
D608	SP	1/50	230	3000	1	0.6	Open Vent.	CW	SLV	1/4 x 1-5/16	3 3/4	I	18
D209	SP	1/30	115	3000	1	1.1	Open Vent.	DS	SLV	3-1/4 x 1/4 x 3-1/4	3 5/8	J	18
D208	SP	1/30	115	3000	1	1.1	Open Vent.	CW	SLV	1/4 x 3	3 5/8	I	18
D214	SP	1/20	115/230	3000	1	1.7-.8	Totally Encl.	CW	SLV	5/16 x 6-1/2	4 5/8	K	18,19
D215	SP	1/20	115/230	3000	1	1.7-.8	Totally Encl.	CCW	BALL	5/16 x 6-1/2	4 5/8	K	18
D220	SP	1/20	115/230	3000	1	1.7-.8	Totally Encl.	CW	BALL	5/16 x 6-1/2	4 5/8	K	18
D218	PSC	1/20	115	3000	1	0.8	Totally Encl.	REV	BALL	5/16 x 2-1/4	4 3/8	L	18,20
D219	PSC	1/8	115	3000	1	1.8	Totally Encl.	REV	BALL	5/16 x 2-1/4	5 1/8	L	18,20
D404	PSC	1/10	208-230	3000	1	0.8	Totally Encl.	REV	BALL	5/16 x 3-1/4	4 1/4	M	15,21
D405	PSC	1/10	115	3000	1	1.4	Open Vent.	REV	BALL	5/15 x 3-1/4	4 1/4	M	15,21
D503	PSC	1/10	230	1500	1	0.95	Open Vent.	REV	SLV	5/16 x 3-3/4	4 5/8	N	15

NOTES: 15: Air Over 16: Skeleton Motor 17: 3.25" Diameter 18: Self-Cooled 19: Popular ice machine pump motor 20: 4M 370V Capacitor included 21: 10M 440V Capacitor included



FIG. A D200, D201



FIG. B D229, D230



FIG. C D202, D203, D206, D210, D216



FIG. D D228



FIG. E D207



FIG. F D213, D211



FIG. G D402, D403



FIG. H D205



FIG. I D608, D208



FIG. J D209



FIG. K D214, D215, D220



FIG. L D218, D219



FIG. M D404, D405



FIG. N D503



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D1127	PSC	1/12-1/15-1/20	115/230	1550	1	1.1/0.6	Open Vent.	REV	SLV	5/16 x 3	3 1/2	A	
D107	SP	1/160	208-240	600	1	0.5	Open Vent.	CCW	SLV	5/16 x 1	2 5/8	B	15
D129	SP	1/125-1/200	115	1500	2	.4-.3	Open Vent.	DS	SLV	3-1/4 x 1/4 x 3-1/4	2 1/8	C	15,22
D1119	SP	1/90	240	1500	1	0.34	Open Vent.	CCW	SLV	1/4 x 1-1/2	2 1/4	D	15
D120	SP	1/70	115	1500	1	0.7	Open Vent.	CW	SLV	1/4 x 2-1/4	2 1/8	E	15
D121	SP	1/70	115	1500	1	0.7	Open Vent.	CCW	SLV	1/4 x 2-1/4	2 1/8	E	15
D1134	SP	1/50-1/65-1/80	115	1500	3	1.1-.8-.6	Open Vent.	CW	SLV	1/4 x 1-3/4	2 1/4	F	15
D609	SP	1/50	115	1500	1	0.9	Open Vent.	CCW	SLV	1/4 x 2-1/4	2 3/16	E	15
D603	SP	1/50	115	1500	1	0.9	Open Vent.	CW	SLV	1/4 x 2-3/8	2 3/16	E	15
D126	SP	1/40	115	1500	1	1.1	Open Vent.	CW	SLV	5/16 x 2-1/4	2 1/2	E	15
D127	SP	1/40	115	1500	1	1	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 1/2	E	15
D128	SP	1/40-1/50-1/80	115	1500	3	1.3-.9-.6	Open Vent.	DS	SLV	4 x 5/16 x 4	2 1/2	C	15
D190	SP	1/40	230	1500	1	0.6	Open Vent.	CW	SLV	1/4 x 2-1/4	2 1/2	E	15
D106	SP	1/40	115	1500	1	0.9	Open Vent.	CCW	SLV	1/4 x 1-3/4	2 1/8	G	15
D105	SP	1/37	115	1500	1	0.94	Open Vent.	CCW	SLV	1/4 x 1-1/2	2 1/8	G	15
D136	SP	1/30	115	1500	1	1.3	Open Vent.	DS	SLV	2 x 5/16 x 2	3 1/4	C	15
D514	SP	1/30	115	1500	1	1.3	Open Vent.	CW	SLV	5/16 x 2-1/4	2 3/4	H	15
D515	SP	1/30	115	1500	1	1.3	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 5/8	H	15
D532	SP	1/30-1/112	115	1500	2	1.4-.8	Open Vent.	CW	SLV	5/16 x 1-1/2	2 3/4	E	15
D181	SP	1/30-1/40	115	1500	2	1.3-1	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 5/8	E	15
D332	SP	1/25-1/65	115	1500	2	1.5-.8	Open Vent.	CW	SLV	5/16 x 2	3 1/4	I	15
D364	SP	1/25	115	1500	1	1.8	Open Vent.	DS	SLV	1-7/8 x 5/16 x 1-7/8	2 7/8	J	15
D365	SP	1/25	115	1500	1	1.8	Open Vent.	DS	SLV	1-7/8 x 5/16 x 1-7/8	2 7/8	K	15,23
D184	SP	1/25	115	1500	1	1.2	Open Vent.	CW	SLV	5/16 x 1-7/8	3	L	15,24
D636	SP	1/25	230	1500	1	0.69	Open Vent.	DS	SLV	2-1/4 x 5/16 x 2-1/4	3 1/4	M	15
D132	SP	1/20	115	1500	1	1.8	Open Vent.	CW	SLV	5/16 x 2-1/4	2 3/4	N	15
D133	SP	1/20	115	1500	1	1.8	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 3/4	N	15
D188	SP	1/20	230	1500	1	0.9	Open Vent.	CW	SLV	5/16 x 2-1/4	2 7/8	N	15

NOTES: 15: Air Over 22: Impedance Protected 23: Has hubs for end rings 24: Closed construction



FIG. A D1127



FIG. B D107



FIG. C D129, D128, D136



FIG. D D1119



FIG. E D120, D121, D609, D603, D126, D127, D190, D532, D181



FIG. F D1134



FIG. G D106, D105



FIG. H D514, D515



FIG. I D332



FIG. J D364



FIG. K D365




FIG. L D184



FIG. M D636



FIG. N D132, D133, D188



Thermally protected • UL recognized • CSA or ULc certified
 NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.

NEW ITEM! See page 113 for a complete listing of all our new products.



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D189	SP	1/20	230	1500	1	0.9	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 7/8	A	15
D186	SP	1/20	460	1500	1	0.4	Open Vent.	CW	SLV	5/16 x 2-1/3	2 7/8	A	15
D109	SP	1/15	115	1600	1	2.1	Open Vent.	CW	SLV	5/16 x 3	3	B	15
▶ D1161	SP	1/15-1/25	115	1500	1	2.9-1.9	Open Vent.	CCW	SLV	5/16 x 2	4 1/4	C	15
▶ D540	SP	1/100	115	1500	1	0.6	Totally Encl.	CW	SLV	1/4 x 2-1/4	2 1/8	D	15
▶ D541	SP	1/100	115	1500	1	0.6	Totally Encl.	CCW	SLV	1/4 x 2-1/4	2 1/8	D	15
▶ D1109	SP	1/100	115	1500	1	0.65	Totally Encl.	CCW	SLV	1/4 x 1-1/4	2 1/16	E	15
▶ D1162	SP	1/100	115	1500	1	0.6	Open Vent.	REV	SLV	5/16 x 1	3 1/2	F	15
▶ D122	SP	1/80	115	1500	1	0.6	Totally Encl.	CW	SLV	1/4 x 2-1/4	2 1/8	G	15
▶ D123	SP	1/80	115	1500	1	0.6	Totally Encl.	CCW	SLV	1/4 x 2-1/4	2 1/8	G	15
▶ D182	SP	1/60	115	1500	1	0.6	Totally Encl.	CW	SLV	5/16 x 2-1/4	2 3/4	G	15
▶ D124	SP	1/50	115	1500	1	0.75	Totally Encl.	CW	SLV	1/4 x 2-1/4	2 1/2	G	15
▶ D125	SP	1/50	115	1500	1	0.75	Totally Encl.	CCW	SLV	1/4 x 2-1/4	2 1/2	G	15
▶ D601	SP	1/50	115	1500	1	0.9	Totally Encl.	CCW	SLV	1/4 x 2-1/4	2 3/16	G	15
▶ D602	SP	1/50	115	1500	1	0.9	Totally Encl.	CW	SLV	1/4 x 2-1/4	2 3/16	G	15
▶ D624	SP	1/50	230	1500	1	0.4	Totally Encl.	CW	SLV	1/4 x 2-1/4	2 1/2	G	15
▶ D1139	SP	1/50-1/80-1/125	115	1500	3	0.88	Open Vent.	CW	SLV	2-1/2 x 5/16 x 1-1/8	2 13/16	H	15
D534	SP	1/35-1/100	115	1500	1	1.4-5	Totally Encl.	CW	SLV	1/4 x 1	2 1/2	I	15
D137	SP	1/30-1/65	115	1500	1	1-.7	Totally Encl.	DS	SLV	3 x 5/16 x 3	2 7/8	J	15
D1118	SP	1/30	240	1500	1	0.6	Open Vent.	CW	BALL	5/16 x 3-1/2	2 13/16	K	15
D1164	SP	1/25	115/230	1550	1	1.3-.65	Totally Encl.	CW	SLV	5/16 x 2-1/2	3 1/8	L	15

NOTES: 15: Air Over



FIG. A D189, D186



FIG. B D109



FIG. C D1161



FIG. D D540, D541



FIG. E D1109



FIG. F D1162



FIG. G D122, D123, D182,
D124, D125, D601,
D602, D624



FIG. H D1139



FIG. I D534



FIG. J D137



FIG. K D1118



FIG. L D1164



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	"C" DIM.	CROSS REF.	FIG.	NOTES
D429	SP	9 Watts	115	1550	1	0.6	Totally Encl.	CCW	SLV	HUB		3	GE 5411	A	25,26,27,28
D431	SP	1/80	230	1550	1	9 Watts	Totally Encl.	CCW	SLV	HUB	2 1/8		GE 5421	B	
D437	SP	16 Watts	115	1550	1	1.1	Totally Encl.	CCW	SLV	HUB		3 7/32	GE 5811	A	25,26,27,28
D477	SP	1/35	208/230	1550	1	0.75	Open Vent.	CCW	SLV	5/16 x 1-5/8	4 1/4		GE 1432	C	29,30
D471	SP	1/20	208-230	1550	1	1.1	Open Vent.	CCW	SLV	5/16 x 2-1/2	4 1/4		GE 1332	C	29,30
D470	SP	1/20	208-230	1550	1	0.94	Open Vent.	CW	SLV	5/16 x 2-5/8	4 1/4		GE 1342	C	29,30
D472	SP	1/20	115	1550	1	1.9	Open Vent.	CW	SLV	5/16 x 2-5/8	4 1/4		GE 1341	C	29,30
D473	SP	1/20	115	1550	1	2	Open Vent.	CCW	SLV	5/16 x 2-5/8	4 1/4		GE 1331	C	29,30
D475	SP	1/12	460	1550	1	0.5	Open Vent.	CCW	SLV	5/16 x 2-1/2	4 1/2			D	29,30,31,32
D498	SP	1/12	460	1550	1	0.5	Open Vent.	CW	SLV	5/16 x 2-1/2	4 1/2			D	29,29,30,32
D469	SP	1/12	208-230	1550	1	1.3	Open Vent.	CCW	SLV	5/16 x 2-1/8	4 1/3		GE 1232	E	29,30

NOTES: 25: Mounting bracket designed to match the original motor (four 8-36 drilled and tapped holes) 26: Mounting hardware included 27: Has 22" leads with 1/16" thick insulation 28: Three studs opposite shaft end are 8-32 on a standard 2.84" bolt circle, 120° apart 29: 3.9" diameter 30: Includes 1/2" studs for mounting 31: See Tecumseh OEM section for cross references 32: Do not have extended hubs or rubber rings for base mount



FIG. A D429, D437



FIG. B D431




FIG. C D477, D471, D470, D472, D473



FIG. D D475, D498



FIG. E D469



NEW ITEM! See page 113 for a complete listing of all our new products.

Thermally protected • UL recognized • CSA or ULc certified

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
BOHN													
D1124	SP	1/20	115	1500	1	2.1	Open Vent.	CW	SLV	5/16 x 3	3	A	33
D1126	SP	1/15	230	1500	1	1.1	Open Vent.	CW	SLV	5/16 x 3	3 1/2	A	33
D1125	PSC	1/12	208-230	1500	1	0.4	Open Vent.	CCW	SLV	5/16 x 2-5/8	3 3/4	B	20,34
KEEPRITE													
D1120	SP	1/20	115	1500	1	2.1	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	C	
D1121	SP	1/20	208-230	1550	1	1.0	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	C	
D1243	PSC	1/20	115	1550	1	0.8	Open Vent.	CCW	SLV	5/16 x 2-3/4	4 1/8	D	
D1245	PSC	1/20	230	1550	1	0.4	Open Vent.	CCW	SLV	5/16 x 2-3/4	4	D	
KRAMER-TRENTON													
D1152	SP	1/20	115	1500	1	1.7	Open Vent.	CW	SLV	5/16 x 2-3/8	2 7/8	E	
D1154	SP	1/20	230	1500	1	1	Open Vent.	CW	SLV	5/16 x 2-3/8	3 1/8	E	
LARKIN COIL													
D1101	SP	1/20	115	1500	1	1.9	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 3/4	E	33
D1103	SP	1/20	208-230	1500	1	1.15	Open Vent.	CCW	SLV	5/16 x 2-1/4	3	E	33
McQUAY													
D1144	PSC	1/25-1/35-1/65	115	1200	3	1.1-9-.6	Open Vent.	CW	SLV	3/8 x 5-3/8	4 3/4	F	35
D1142	SP	1/15	115/230	1500	1	1.7-9	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	G	34
SINGER													
▶ D1164	SP	1/25	115/230	1550	1	1.3-.65	Totally Encl.	CW	SLV	5/16 x 2-1/2	3 1/8	H	
WITT													
D1102	PSC	1/20	115/230	1550	1	.75-.4	Open Vent.	CW	SLV	5/16 x 2-5/8	3 1/2	I	

NOTES: 20: 4M 370V Capacitor included 33: Shell Turbo 68, low temp. oil (-40°F) 34: Bolt Circle = 3.15" 35: PSC use 4M 370V Capacitor



FIG. A D1124, D1126



FIG. B D1125



FIG. C D1120, D1121



FIG. D D1243, D1245



FIG. E D1152, D1154, D1101, D1103



FIG. F D1144



FIG. G D1142



FIG. H D1164



FIG. I D1102

FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D134	SP	1/25	115	1500	1	1.6	Totally Encl.	CW	SLV	5/16 x 2-1/4	4 1/4	A	
D1138	SP	1/50-1/80-1/140	115	1500	3	.9-.6-.5	Open Vent.	CW	SLV	5/16 x 2-1/2	4	B	
D135	SP	1/25	115	1500	1	1.6	Totally Encl.	CCW	SLV	5/16 x 2-1/4	4 1/4	A	
D192	SP	1/25	230	1500	1	0.9	Totally Encl.	CW	SLV	5/16 x 2-1/4	4 1/4	C	
D226	SP	1/20	115	1500	1	1.6	Totally Encl.	CW	BALL	5/16 x 2-1/4	4 1/4	C	
D227	SP	1/20	115	1500	1	1.7	Totally Encl.	CCW	BALL	5/16 x 2-1/4	4 1/4	A	
D334	SP	1/15	230	1500	1	1.4	Totally Encl.	CW	BALL	5/16 x 3	4 3/4	C	
D234	SP	1/15	115	1500	1	2.2	Totally Encl.	CW	SLV	5/16 x 2-1/4	4 3/4	C	
D235	SP	1/12	115	1500	1	2.2	Totally Encl.	CCW	SLV	5/16 x 2-1/4	4 3/4	C	
D138	SP	1/25	115	1500	1	1.6	Totally Encl.	CW	SLV	5/16 x 2-5/8	4 1/2	D	
D238	SP	1/15	115	1500	1	2.3	Totally Encl.	CW	SLV	5/16 x 2-5/8	4 1/2	D	36
D167	SP	1/70	115	1500	1	0.7	Open Vent.	CW	SLV	1/4 x 3	2 7/8	E	
D169	SP	1/70	115	1500	1	0.7	Open Vent.	CCW	SLV	1/4 x 3	3	E	
D130	SP	1/40	115	1500	1	1	Open Vent.	CW	SLV	5/16 x 4-1/8	3 1/3	E	
D131	SP	1/40	115	1500	1	1	Open Vent.	CCW	SLV	5/16 x 2-1/4	3 1/3	E	
D330	SP	1/40	230	1500	1	0.5	Open Vent.	CW	SLV	5/16 x 2-1/4	3 7/8	E	
D1173	SP	1/30	115	1500	1	1.2	Open Vent.	CW	BALL	5/16 x 2-1/2	3 7/8	F	
D504	PSC	1/8	115/230	1500	1	1.6-.8	Open Vent.	REV	SLV	5/16 x 3-1/2	5 1/2	G	37,38

NOTES: 36: With conduit box 37: PSC motor requiring a 10M 370V Capacitor 38: 3.91" diameter



FIG. A D134, D135, D227



FIG. B D1138



FIG. C D192, D226, D334, D234, D235



FIG. D D138, D238




FIG. E D167, D169, D130, D131, D330



FIG. F D1173



FIG. G D504



Thermally protected • UL recognized • CSA or ULc certified
NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.

3.3" Diameter



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D1111	SP	1/18-1/30	115	1330	2	2.4-1.2	Open Vent.	CCW	SLV	3-1/8 x 5/16 x 2-3/8	3 1/2	A	39
D366	SP	1/14-1/25	115	1550	2	2.5-1.5	Open Vent.	DS	SLV	6-3/8 x 5/16 x 6-3/8	3 1/4	B	
D367	SP	1/12-1/20-1/30	115	1550	3	3-2.1-1.7	Open Vent.	DS	SLV	5-3/4 x 5/16 x 5-3/4	3 5/8	B	
D325	SP	1/10-1/30	115	1550	2	2.5-2.3	Open Vent.	CCW	SLV	1-3/4 x 5/16 x 2-3/8	3 1/2	C	39
D1176	PSC	1/15-1/25	115	1550	2	1-.8	Totally Encl.	DS	SLV	4-7/8 x 3/8 x 4-7/8	4	D	40
D323	PSC	1/15-1/20-1/35	115	1550	3	1-.8-.6	Totally Encl.	DS	SLV	2-3/4 x 5/16 x 2-3/4	3 3/4	E	41,42
D1112	PSC	1/15-1/20-1/25	115	1550	3	1.5-1-.9	Open Vent.	CW	SLV	2-5/8 x 5/16 x 2-7/8	4	F	39,42,43
D326	PSC	1/10-1/20-1/25	115	1550	3	2.2-1.8-1.5	Open Vent.	DS	BALL	5-1/2 x 5/16 x 3	4 1/8	G	44

NOTES: 39: Rotation determined by viewing lug end 40: 4M 370V Capacitor 41: Totally enclosed, Sears-Whirlpool 5000-8000 BTU units. 42: 3M 370V Capacitor 43: Wiring slightly different from OEM PSC; check nameplate connection diagram. Capacitor and Bracket included. Replaces 2 and 3 speed SP and PSC motor. Motor in Gibson/Belding window units. 44: 4M 370V Capacitor (similar to GE WJ94X306)



FIG. A D1111



FIG. B D366, D367



FIG. C D325



FIG. D D1176



FIG. E D323



FIG. F D1112



FIG. G D326



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D222	SP	1/25	115	1500	1	1.6	Totally Encl.	DS	SLV	2-1/4 x 5/16 x 2-1/4	2 7/8	A	15
D520	SP	1/20-1/50-1/100	115	1500	3	2-1-.6	Totally Encl.	CW	SLV	1/4 x 2-1/4	3 1/8	B	15,45,46
D1186	PSC	1/16	460	3450	1	0.3	Open Vent.	CCW	BALL	5/16 x 3-1/3	4 3/4	C	40
D1184	PSC	1/16	460	3450	1	0.3	Open Vent.	CCW	BALL	5/16 x 3-1/3	4 3/4	C	40,47
D410	PSC	1/10	115	3000	1	1.5	Open Vent.	REV	BALL	1/4 x 3-3/4	7 1/8	D	48,49,50,51
D412	PSC	1/9	230	3000	1	0.7	Open Vent.	REV	BALL	1/4 x 3-3/4	6 5/8	D	40,49,50,51
D418	SP	1/50	115	1550	1	1.1	Open Vent.	CW	BALL	1/4 x 3	5 1/2	E	50,51
D415	SP	1/40	115	1550	1	1.1	Open Vent.	CCW	BALL	1/4 x 3	5 1/2	E	50,51
D1191	SP	1/40	460	3200	1	0.37	Open Vent.	CCW	BALL	1/4 x 2-1/2	5 3/4	F	49,50,51
D1192	SP	1/40	115	3000	1	0.7	Open Vent.	CCW	SLV	5/16 x 1-1/2	5 1/3	G	51
D1196	SP	1/33	115	3200	1	1.5	Open Vent.	CCW	SLV	5/16 x 2-1/3	3 1/4	H	50
D1198	SP	1/30	115	3200	1	1.5	Open Vent.	CCW	SLV	5/16 x 2-1/4	3 1/8	I	50
D1194	SP	1/25	115	3200	1	1.7	Open Vent.	CW	BALL	5/16 x 1-1/3	5 1/2	J	51
D1193	SP	1/22	115	3000	1	1.2	Open Vent.	CCW	SLV	5/16 x 2-1/3	2 7/8	K	50
D1188	SP	1/15	208-230/460	3000	1	1.1-1.6	Open Vent.	CW	BALL	5/16 x 2	6 5/8	L	50,51
D408	SP	1/150	115	3000	1	0.5	Open Vent.	CW	SLV	1/4 x 1-1/2		M	49,51,52
D1167	SP	1/40	208-230	3000	1	0.55	Open Vent.	CCW	SLV	5/16 x 1		N	51
D455	SP	1/30	115/230	3000	1	1.3-1.7	Open Vent.	CCW	BALL	1/4 x 3-7/8		O	49,51

NOTES: 15: Air Over 40: 4M 370V Capacitor 45: Mechanically Reversible 46: Endshield on D520 is easily removed, allowing rotor and shaft to be rotated, thereby reversing motor rotation. 47: Has Hall Effect sensor 48: 7.5M 370V Capacitor 49: Motors include shaft bushing 50: Stainless steel shaft 51: Includes centrifugal switch 52: Drilled & Tapped Holes (No. 8-32NC) in face of case at shaft end for mounting in various Coleman mobile home furnace applications, also has mounting studs.



FIG. A D222



FIG. B D520



FIG. C D1186, D1184



FIG. D D410, D412



FIG. E D418, D415



FIG. F D1191



FIG. G D1192



FIG. H D1196



FIG. I D1198



FIG. J D1194



FIG. K D1193



FIG. L D1188




FIG. M D408



FIG. N D1167



FIG. O D455



Thermally protected • UL recognized • CSA or ULc certified
 NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.

3.3" Diameter

Flue Exhaust and Draft Booster Blower Motors



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D454	SP	1/30	115	3000	1	1.5	Open Vent.	CW	SLV	1/4 x 1-1/2		A	49,51,53
D456	SP	1/15	115/230	3000	1	2-1	Totally Encl.	CW	BALL	1/4 x 2-3/4		B	49,50,51
D458	SP	1/15	208-230	3000	1	1	Open Vent.	CW	BALL	1/4 x 2-3/4		B	49,50,51
D457	SP	1/15	115/230	3000	1	2-1	Open Vent.	CCW	BALL	1/4 x 2-3/4		B	49,50,51
D1174	SP	1/15	460	3000	1	0.6	Open Vent.	CW	BALL	1/4 x 2-1/2		B	49,51
D1171	SP	1/15	460	3000	1	0.6	Open Vent.	CCW	BALL	1/4 x 2-1/2		B	49,51
D1169	SP	1/10	208-230	3000	1	1.5	Open Vent.	CCW	SLV	5/16 x 1		C	51
D1179	SP	1/30	115	3000	1	1.5	Open Vent.	CW	SLV	5/16 x 2		D	50
D1190	SP	1/30	115	3000	1	1.6	Open Vent.	CW	SLV	5/16 x 1-3/4		E	50
D1180	SP	1/20	115	3300	1	1.9	Open Vent.	CW	SLV	5/16 x 2-1/8		D	50

NOTES: 49: Motors include shaft bushing 50: Stainless steel shaft 51: Includes centrifugal switch 53: Used in Economite, "E-20," LS1/Miller and Mid Continent gas units.



FIG. A D454



FIG. B D456, D458, D457, D1174, D1171



FIG. C D1169



FIG. D D1179, D1180



FIG. E D1190