



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
D1061	SP	1/20-1/30-1/60	115	1500	3	2-1.7-1.4	Open Vent.	CCW	SLV	1/2 x 2-3/4	4 1/8	A	54
D170	SP	1/20	115	1500	1	1.7	Open Vent.	CW	SLV	5/16 x 2-1/4	2 3/4	B	55
D116	SP	1/15	115	1500	1	2.4	Open Vent.	CW	SLV	3/8 x 2-3/8	3	B	
D118	SP	1/15-1/30	115	1500	2	2.4-1.4	Open Vent.	CW	SLV	3/8 x 2-3/8	3	B	
D1170	SP	1/15	115	1500	1	2.1	Open Vent.	CW	BALL	3/8 x 2-1/2	4 3/4	C	56
D377	SP	1/12	115	1500	1	3.1	Open Vent.	CCW	SLV	3/8 x 2	2 3/4	B	57
D310	SP	1/12	115	1500	1	4	Open Vent.	CW	SLV	3/8 x 2	2 3/4	B	58
D119	SP	1/11-1/25-1/70	115	1500	3	2.9-1.5-1	Open Vent.	CCW	BALL	1/2 x 2-5/8	3 3/4	D	59
D174	SP	1/10	115	1500	1	3.5	Open Vent.	CW	SLV	3/8 x 2-7/8	3 3/8	E	
D674	SP	1/10-1/15	230	1500	2	2-1.3	Open Vent.	CW	SLV	3/8 x 2-1/2	3 5/8	B	
D1039	SP	1/10	115	1500	1	3.1	Open Vent.	CCW	SLV	1/2 x 2-3/8	4 1/2	F	60
D374	SP	1/8-1/20	115	1500	2	4-2.5	Open Vent.	CW	SLV	3/8 x 2-1/2	3 5/8	B	
D312	SP	1/15	115	1500	1	2.7	Open Vent.	CW	SLV	1/2 x 5	4 1/4	G	61,62
D112	SP	1/10	115	1500	1	3.6	Open Vent.	CW	SLV	3/8 x 2-5/8	4 1/2	G	62
D435	SP	1/10	230	1500	1	1.7	Open Vent.	CCW	SLV	3/8 x 2-5/8	4 1/2	G	62

NOTES: 54: For use with Greenheck Fan 55: Shaft stepped down from 3/8" dia. shaft 56: OEM direct replacement for Jenn Air 80CR 57: Used in Jenn Air units P/N 7108-2101 58: Used in Leslie-Locke ventilators P/N 7108-5056 59: Used in Acme Eng. Roof Vents 60: ILG ventilator 7108-2171. Has internal fan. 61: External oil retainer to accommodate resilient rings and cradle base, drilled and tapped holes in case for mounting in Coleman applications. (2 holes each end on case OD). 62: Self cooled for mechanical duty



FIG. A D1061



FIG. B D170, D116, D118, D377, D310, D674, D374



FIG. C D1170



FIG. D D119




FIG. E D174



FIG. F D1039



FIG. G D312, D112, D435



Thermally protected • UL recognized • CSA or ULc certified
 NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.

4.4" Diameter

Fan Coil Air-Conditioning and Heating Unit Motors



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.
D333	SP	1/25	115	1550	1	1.4	Open Vent.	DS	SLV	7-1/4 x 3/8 x 7-1/4	2 7/8	A
D335	SP	1/20-1/30-1/40-1/60	115	1550	4	2.1-1.4-1.2-1.1	Open Vent.	DS	SLV	8 x 1/2 x 8	3 1/4	A
D117	SP	1/15-1/25-1/30-1/40	115	1550	4	2.4-1.4-1.1-.9	Open Vent.	CCW	SLV	1/2 x 7-1/2	3	B
D329	SP	1/15	115	1550	1	2.5	Open Vent.	DS	SLV	7-1/2 x 3/8 x 7-1/2	3 3/8	C
D236	SP	1/10-1/15-1/25	115	1550	3	3.5-2.4-1.8	Open Vent.	DS	SLV	7-1/2 x 1/2 x 7-1/2	3 3/8	D
D336	SP	1/10-1/15-1/25	115	1550	3	3.5-2.4-1.8	Open Vent.	DS	SLV	7-1/2 x 3/8 x 7-1/2	3 1/2	D
D635	SP	1/10-1/20-1/35	230	1550	3	1.8-1.3-1	Open Vent.	DS	SLV	10 x 1/2 x 10	3 3/8	D
D337	SP	1/8-1/10-1/12-1/15	115	1550	4	4.1-2.7-2.3-1.9	Open Vent.	DS	SLV	7-1/2 x 1/2 x 7-1/2	3 5/8	D
D339	SP	1/8-1/12	230	1550	2	2-1.4	Open Vent.	DS	SLV	6-1/2 x 1/2 x 6-1/2	4 1/8	D
D338	SP	1/6-1/10-1/12-1/15	115	1550	4	5.4-3.2-2.5-2.1	Open Vent.	DS	SLV	7-1/4 x 1/2 x 7-1/4	4 1/8	D
D1006	SP	1/4	115	1600	1	7.2	Open Vent.	CW	SLV	1/2 x 2-3/4	4 1/8	E
▶ D113	SP	1/12	115/230	1550	1	2.5-1.3	Totally Encl.	CCW	SLV	3/8 x 3	4 1/8	F
▶ D114	SP	1/12	115/230	1550	1	2.5-1.3	Totally Encl.	CW	SLV	3/8 x 3	4 1/8	F
▶ D115	SP	1/12	115/230	1550	1	2.5-1.3	Totally Encl.	CCW	SLV	1/2 x 2	4 1/8	F



FIG. A D333, D335



FIG. B D117



FIG. C D329



FIG. D D236, D336, D635, D337, D339, D338



FIG. E D1006



FIG. F D113, D114, D115




FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	CROSS REF.	FIG.	NOTES
D484	SP	1/20	115/208-230	1550	1	2.2-1.1	Open Vent.	CW	SLV	3/8 x 3-1/8	4	GE 2341, 2342	A	45,63,64,65
D482	SP	1/15	115/208-230	1550	1	3.2-1.6	Open Vent.	CW	SLV	3/8 x 3-1/8	4	GE 2241, 2242	A	45,63,64,65
D480	SP	1/10	115/208-230	1550	1	4.5-2.2	Open Vent.	CW	SLV	3/8 x 3-1/8	4 5/8	GE 2141, 2142	A	45,63,64,65
D485	SP	1/20	115/208-230	1550	1	2.2-1.1	Open Vent.	CCW	SLV	3/8 x 3-1/8	4	GE 2331, 2332	A	45,63,64,65
D483	SP	1/15	115/208-230	1550	1	3.2-1.6	Open Vent.	CCW	SLV	3/8 x 3-1/8	4	GE 2231, 2232	A	45,63,64,65
D481	SP	1/10	115/208-230	1550	1	4.5-2.2	Open Vent.	CCW	SLV	3/8 x 3-1/8	4 5/8	GE 2131, 2132	A	45,63,64,65

NOTES: 45: Mechanically Reversible 63: Can be operated on 50Hz with air-over applications 64: 3/8" shaft diameter with adapter to convert to 1/2" diameter 65: Weld nuts on a 3.5" B.C. for stud mount



FIG. A D484, D482, D480, D485, D483, D481



Thermally protected • UL recognized • CSA or ULc certified
 NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.