



Model RVW62

ASME HOT WATER SAFETY RELIEF VALVE (10-620/630 Series)

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

DESCRIPTION

The Apollo® RVW62 is an ASME Section IV capacity certified bronze safety relief valve for protection of hot water heating boilers, swimming pool heaters and similar equipment. It can be pre-set to any pressure ranging between 30 to 150 psig (2.1 to 10.3 bar).

FEATURES

- ASME Section IV (HV) Certified Capacity
- 30-150 psig Set Pressure Range
- Corrosion Resistant Construction
- Diaphragm Isolated Spring Chamber
- Male or Female NPT Inlet
- MADE IN THE USA

MATERIALS

Body: ASTM B 584 Bronze
 Bonnet: ASTM B584 Bronze
 Diaphragm: Reinforced EPDM
 Spring: Stainless Steel
 Seat: Silicone

CAPACITY

ASME HV Rating – 90% of actual capacity at 10% overpressure

Set Pressure		Capacity	
Psig	Bar	BTU/HR	
30	2.07	689,000	
50	3.45	1,007,000	
75	5.17	1,405,000	
100	6.90	1,802,000	
125	8.62	2,199,000	
150	10.34	2,597,000	

DIMENSIONS

Series (Model)	SIZE	Height		Width		Weight	
	In x Out	in.	mm	in.	mm	lbs	kgs
10624 (RVW62)	3/4M x 3/4F	4.6	117	2.35	60	1.0	.48
10634 (RVW62F)	3/4F x 3/4F	4.5	114	2.35	60	1.0	.48



OPTIONS

- 3/4" Male NPT inlet (RVW62)
- 3/4" Female NPT inlet (RVW62F)
- Set Pressure (psig) (30-150)

APPROVALS



ASME Section IV – Heating Boilers
 Canadian Registration Number 0G8547.5C

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold.