



Main

| | |
|---------------------------------------|------------------------------------|
| Range of product | 8501K |
| Product or component type | Relay |
| Contacts material | Silver alloy (AgNi) |
| Switch function | DPDT |
| [Uc] control circuit voltage | 120 V AC |
| Rated power in hp | 1 hp 277 V 0.33 hp 120 V |
| Maximum switching voltage | 300 V AC 30 V DC |
| Ambient air temperature for operation | -40...131 °F |
| Shape of pin | Spade |
| Product certifications | CE CSA RoHS UL recognized |
| Operating time | 20 ms pick-up 20 ms drop-out |
| Relay type | General purpose |

Ordering and shipping details

| | |
|-----------------------|-----------------|
| Category | 21144 - 8501 KU |
| Discount Schedule | CP2 |
| GTIN | 00785901310334 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.19 |
| Country of origin | CN |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1418 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |