



### Main

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Range of product                      | 8501R                              |
| Product or component type             | Miniature Relay                    |
| Contacts material                     | Silver tin oxide                   |
| Switch function                       | DPDT                               |
| [Uc] control circuit voltage          | 120 V AC                           |
| Rated power in HP                     | 0.33 120 V<br>0.5 240 V            |
| Mounting support                      | Socket                             |
| Ambient air temperature for operation | -40...158 °F                       |
| Shape of pin                          | Spade                              |
| Product certifications                | CE<br>CSA<br>RoHS<br>UL recognized |
| Operating time                        | 25 ms pick-up<br>20 ms drop-out    |
| Local signalling                      | No indicator                       |
| Control type                          | Without                            |
| Product compatibility                 | 8501NR42                           |
| Relay type                            | Standard                           |

### Ordering and shipping details

|                       |                      |
|-----------------------|----------------------|
| Category              | 21143 - 8501 R       |
| Discount Schedule     | CP2                  |
| GTIN                  | 00785901131311       |
| Nbr. of units in pkg. | 1                    |
| Package weight(Lbs)   | 8.999999999999997E-2 |

|                   |    |
|-------------------|----|
| Country of origin | CN |
|-------------------|----|

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1418 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|