Product data sheet Characteristics

8910DPA33V14 CONTACTOR 600VAC 30AMP DPA +OPTIONS





Main

Product or component type	Definite Purpose Contactor	
Line Rated Current	30 A	
Poles description	3P	
Pole contact composition	3 NO	
Range of product	DPA	±

Complementary

Complementary		
Motor power hp	2 hp 115 V AC 1 phase 5 hp 230 V AC 1 phase 10 hp 230 V AC 3 phases 15 hp 460 V AC 3 phases 20 hp 575 V AC 3 phases	in a primirity programmi imparation in the programmi in the programmi imparation in th
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC	
System Voltage	600 V AC	9.
Control circuit voltage	24 V AC 50/60 Hz	
Phase	3 phases	
Electrical connection	Quick connect terminals Binder head	

Environment

Livitoriiione		2.
Product certifications	CE	
	CSA	. <u>v</u>
	UL listed	. <u>.</u>
	02	<u> </u>

Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)	F
Discount Schedule	CP1B	

GTIN	00785901073543	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1.01	
Country of origin	CN	
Offer Sustainability		
Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
REACh	Reference not containing SVHC above the threshold	
Reference not containing SVHC above the threshold		

Contractual warranty

Warranty period	18 months	
Warranty period	18 months	