



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Poles description	4P
Pole contact composition	4 NO
Range of product	DPA

### Complementary

Motor power hp	2 hp 115 V AC 1 phase 5 hp 230 V AC 1 phase 10 hp 230 V AC 3 phases 15 hp 460 V AC 3 phases 20 hp 575 V AC 3 phases
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
System Voltage	600 V AC
Control circuit voltage	24 V AC 50/60 Hz
Phase	3 phases
Electrical connection	Quick connect terminals Binder head

### Environment

Product certifications	CE CSA UL listed
------------------------	------------------------

### Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)
Discount Schedule	CP1B

GTIN	00785901073512
Nbr. of units in pkg.	1
Package weight(Lbs)	1.3100000000000001
Country of origin	CN

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

### Contractual warranty

Warranty period	18 months
-----------------	-----------