



Robertshaw®



700-402

GAS VALVES

700 Series - 24 Volt Combination

The Robertshaw® 700 Series 24 Volt Combination Gas Valves offer replacement flexibility. With capacities ranging to 720,000 BTU, three-position outlets and multi-positional capability, these combination gas valves offer unlimited replacement possibilities. The 24 Volt Uni-Kit® models are suitable for either natural or LP gas. The valve is factory set at 3.5" WC natural gas. A regulator cover plate is included to convert to LP gas.

Features and Benefits

- Gas cock dial marking Off - Pilot - On
- Pilot outlet 1/4" tubing
- Ambient temperature of -40°F to 175°F
- Combination screw/spade terminal type
- Maximum inlet pressure 14" WC (0.5 PSI)
- Standard NEMA terminals
- Inlet filtered screen
- Various gas types: natural, manufactured, mixed, LP, and LP/air mixtures
- Multiple actuators available
- RoHS compliant

Specifications

| Part Numbers | Description | Capacity | Inlet Size | Outlet Size | Side Outlets | Pressure Regulator Setting | Electrical Rating | Comments |
|--------------|---------------------|-------------|------------|-------------|---------------|----------------------------|---------------------------------------|--|
| 700-400 | 24 Volt Combination | 240,000 BTU | 1/2" | 3/4" | Straight-thru | Uni-Kit® Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | NA |
| 700-402 | 24 Volt Combination | 240,000 BTU | 1/2" | 3/4" | 1/2" | Uni-Kit Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | NA |
| 700-406 | 24 Volt Combination | 300,000 BTU | 3/4" | 3/4" | Straight-thru | Uni-Kit Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | NA |
| 700-409 | 24 Volt Combination | 240,000 BTU | 1/2" | 1/2" | Straight-thru | 3.5" WC Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | Thermopile type safety magnet |
| 700-426 | 24 Volt Combination | 300,000 BTU | 3/4" | 3/4" | Straight-thru | 3.5" WC Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | Slow opening feature for soft ignition |
| 700-442 | 24 Volt Combination | 720,000 BTU | 1" | 1" | Straight-thru | 3.5" WC Natural Gas | 24V AC @ 0.2 Amps, 12V DC @ 0.18 Amps | Slow opening feature for soft ignition |

RoHS



1 Year Limited Warranty

D4