

General Purpose Single Phase Open Dripproof (ODP), Split Phase



APPLICATIONS:

For commercial and industrial ventilation systems.

FEATURES:

- 40°C Ambient
- 60 Hertz
- Reversible Rotation
- Continuous Duty
- Class A or B Insulation
- Ball Bearing

Single Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	Shaft Dim. (inches)	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6	1200	115	48Z	D16B3N4Z9	\$274	DS-3FMP	1.35	1/2" x 1.875"	10.4	17	4	20, 25
1/4	1800	115	48	D14B2N49	\$143	DS-3FMP	1.35	1/2" x 1.5"	8.4	14	5.1	25
	1800	115	56Z	D14B2NZA9	\$172	DS-3FMP	1.00	1/2" x 1.5"	9.4	15	5.4	20, 25
	1200	115	56	D14B3N9	\$326	DS-3FMP	1.35	1/2" x 1.5"	9.7	25	5.4	21, 25
	1200	208-230	56	7998	\$379	DS-3FMP	1.35	1/2" x 1.5"	14.0	25	2.9	24
1/3	1800	115	48	D13B2N4A9	\$152	DS-3FMP	1.00	1/2" x 1.5"	9.4	15	6.8	25
	1800	115	48Z	D13B2N4Z9	\$207	DS-3FMP	1.35	1/2" x 1.875"	9.3	16	6.5	20, 25
	1800	115	56Z	D13B2NZA9	\$172	DS-3FMP	1.00	1/2" x 1.875"	9.8	15	6	25
	1800	230	48	D13B2K4A9	\$167	DS-3FMP	1.00	1/2" x 1.5"	9.4	15	3	25
	1200	115/230	56	D13B3P9	\$379	DS-3FMP	1.35	1/2" x 1.5"	9.8	25	7.5/3.8	21, 25
1/2	1800	115	48	D12B2N49	\$269	DS-3FMP	1.00	1/2" x 1.5"	9.4	18	8.8	25
	1800	115	56	D12B2NA9	\$241	DS-3FMP	1.00	1/2" x 1.5"	9.7	21	8.6	25
	1800	115	56Z	D12B2NZA9	\$222	DS-3FMP	1.00	1/2" x 1.875"	9.1	18	8.1	25
3/4	1800	115	56	D34B2N9	\$295	DS-3FMP	1.00	1/2" x 1.5"	9.6	21	11.0	25

Two Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	Shaft Dim. (inches)	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3-1/9	1800/1200	115	48	D13B10N49	\$229	DS-3FMP	1.00	1/2" x 1.5"	10.4	19	6.4/4.0	20, 25
	1800/1200	115	56Z	3053	\$327	DS-3FMP	1.00	1/2" x 1.5"	9.9	19	7.1	25
1/2-1/6	1800/1200	115	56	3306	\$420	DS-3FMP	1.00	1/2" x 1.5"	10.8	26	9.2	25

Single Speed, Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	Shaft Dim. (inches)	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115	48Z	D14B2N4Z	\$119	DS-3FMP	1.15	1/2" x 2.25"	9.3	14	5.1	20, 25
1/3	1800	115	48	D13B2N4A	\$146	DS-3FMP	1.00	1/2" x 1.5"	9.4	16	6.8	25
	1800	115	48	D13BA2N4A	\$195	DS-3FMP	1.35	1/2" x 1.5"	9.4	16	6	24
	1800	115	48Z	D13B2N4Z	\$122	DS-3FMP	1.15	1/2" x 2.25"	9.3	14	5.9	20, 25
	1800	115	56Z	2911	\$231	DS-3FMP	1.00	1/2" x 1.5"	9.4	17	6.0	25
1/2	1800	115	48	D12B2N4	\$234	DS-3FMP	1.00	1/2" x 1.5"	9.8	18	8.8	25

Note 20 Stud Extensions in 3 5/8" Square Pattern
 Note 21 Stud Extensions in 4 3/16" Square Pattern

Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-protected

