

General Purpose Single Phase Open Dripproof (ODP) Rigid Base, Capacitor Start



APPLICATIONS:

For air compressors, pumps, conveyors, blowers and general industrial equipment

FEATURES:

- Double Shielded Ball Bearings
- Rigid Base Standard
- Class B Insulation
- Continuous Duty
- 40°C Ambient
- F1 Assembly
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	3600	115/230	48	6335	\$267	DS-3FMP	1.35	9.2	16	6.8/3.4	24
	1800	115/208-230	48	D13C2J4	\$316	DS-3FMP	1.35	8.7	22	8.8/3.8-4.3	25
	1800	115/230&110/220	48	6349	\$419	DS-3FMP	1.35	9.5	20	6.5/3.3 & 7.3/3.6	24, 98
1/2	1800	115/208-230	48	D12C2J4	\$376	DS-3FMP	1.25	9.2	24	10.3/4.8-5.3	25
	1800	115/208-230	56	D12C2J	\$383	DS-3FMP	1.25	11.9	27	9.0/4.3-4.5	25
	1800	115/208-230	56	D12CM2J	\$406	DS-3FMP	1.25	10.9	29	9.0/4.3-4.5	24
	1800	115/208-230	56	D12CA2J	\$389	DS-3FMP	1.25	10.9	20	9.0/4.3-4.5	24
	1800	115/230	48	6343	\$467	DS-3FMP	1.25	9.5	20	8.2/4.1	24
3/4	3600	115/208-230	56	D34C1J	\$319	DS-3FMP	1.25	11.4	27	10.4/5.3-5.2	25
	3600	115/208-230	56	D34CM1J	\$396	DS-3FMP	1.25	11.4	23	10.4/5.3-5.2	23
	1800	115/208-230	56	D34C2J	\$471	DS-3FMP	1.25	9.0	27	11.4/5.7	25
	1800	115/208-230	56	D34CA2J	\$482	DS-3FMP	1.25	11.4	25	11.4/5.7-5.7	24
	1800	115/208-230	56	D34CM2J	\$510	DS-3FMP	1.25	11.4	24	11.4/5.7-5.7	23
	1200	115/208-230	56H	D34C3JH	\$597	DS-3FMP	1.15	12.9	38	10.6/5.4-5.3	25
1	3600	115/208-230	56	D1C1J	\$427	DS-3FMP	1.25	11.4	31	14.6/6.9-7.3	25
	3600	115/208-230	56	D1CM1J	\$448	DS-3FMP	1.25	11.4	31	14.6/6.9-7.3	23
	1800	115/208-230	143T	D1C2J14	\$476	DS-3SP	1.15	12.3	32	14.8/7.5-7.3	25
	1800	115/208-230	143T	D1CA2J14	\$515	DS-3SP	1.15	12.3	30	14.8/7.5-7.3	24
	1800	115/208-230	143T	D1CM2J14	\$538	DS-3SP	1.15	12.3	35	14.8/7.5-7.3	23
	1800	115/208-230	56H	D1C2JH	\$529	DS-3FMP	1.15	11.9	28	14.8/7.5-7.3	25
	1800	115/208-230	56H	D1CA2JH	\$537	DS-3FMP	1.15	11.9	28	14.8/7.5-7.3	24
	1800	115/208-230	56H	D1CM2JH	\$538	DS-3FMP	1.15	11.9	31	14.8/7.5-7.3	23
	1800	115/230	182	D1C2P18Z	\$843	DS-3SP	1.25	12.8	69	14.4/7.2	25
	1200	115/208-230	56H	D1C3JH	\$653	DS-3FMP	1.15	13.4	44	12.6/6.4-6.3	25
1-1/2	3600	115/208-230	143T	D32C1J14	\$474	DS-3FMP	1.15	12.3	31	18.6/9.8-9.3	25
	3600	115/208-230	56H	D32C1JH	\$474	DS-3FMP	1.15	11.9	31	18.6/9.8-9.3	25
	3600	115/208-230	56H	D32CM1JH	\$543	DS-3FMP	1.15	11.9	32	18.6/9.8-9.3	23
	1800	115/208-230	145T	D32C2J14	\$632	DS-3SP	1.15	13.3	39	19.2/10.0-9.6	25
	1800	115/208-230	145T	D32CM2J14	\$630	DS-3SP	1.15	13.3	39	19.2/10.0-9.6	23
	1800	115/208-230	56H	D32C2JH	\$689	DS-3FMP	1.15	12.9	37	19.2/10.0-9.6	25
	1800	115/208-230	56H	D32CA2JH	\$638	DS-3FMP	1.15	12.9	40	19.2/10.0-9.6	24
	1800	115/208-230	56H	D32CM2JH	\$653	DS-3FMP	1.15	12.9	37	19.2/10.0-9.6	23
	1800	115/230	184	D32C2P18Z	\$955	DS-3SP	1.15	13.3	71	22.0/11.0	25
	2	3600	115/208-230	145T	D2C1J14	\$714	DS-3SP	1.15	12.8	36	22.4/12.4-11.2
3600		115/208-230	56H	D2C1JH	\$620	DS-3FMP	1.15	12.4	35	22.4/12.4-11.2	25
3600		115/208-230	56H	D2CM1JH	\$689	DS-3FMP	1.15	12.89	35	22.4/12.4-11.2	23

Note 23 Manual Reset Thermal Overload Protector
Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-Protected
Note 98 50/60 Hz Motor



General Purpose Single Phase Open Dripproof (ODP) Rigid Base, Capacitor Start



HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
2	1800	115/208-230	145T	D2CA2J14	\$792	DS-3SP	1.15	14.25	42	20.0/11.3-10.0	24
	1800	115/208-230	145T	D2C2J14	\$762	DS-3SP	1.15	13.75	42	20.0/11.3-10.0	25
	1800	115/208-230	145T	D2CM2J14	\$815	DS-3SP	1.15	14.25	42	20.0/11.3-10.0	23
	1800	115/208-230	56H	D2CA2JH	\$790	DS-3FMP	1.15	13.89	41	20.0/11.3-10.0	24
	1800	115/208-230	56H	D2CM2JH	\$815	DS-3FMP	1.15	13.89	42	20.0/11.3-10.0	23
	1800	115/230	182T	D2C2P18	\$728	DS-3SP	1.15	14.75	70	23.2/11.6	25
	1800	115/230	213	D2C2P21Z	\$1,212	DS-3SP	1.15	15.02	75	24.6/12.3	25
3	3600	115/230	182	D3C1P18	\$982	DS-3SP	1.15	17.25	81	32.0/16.0	25
	3600	230	56	D3CM1K	\$817	DS-3FMP	1.00	12.43	121	15.0	23
	1800	115/230	184T	D3C2P18	\$918	DS-3SP	1.15	15.75	76	38.0/19.0	25
5	3600	230	184T	D5C1K18	\$1,011	DS-3SP	1.15	18	82	19.6	25
	1800	230	184T	D5C2K18	\$1,389	DS-3SP	1.15	16.25	86	22.0	25
	1800	230	213T	D5C2K21	\$1,394	DS-3SP	1.15	19.13	86	22.0	25
	1800	230	215	D5C2K21Z	\$2,028	DS-3SP	1.15	19.13	86	22.0	25
7-1/2	3600	230	213T	D7C1K21	\$1,265	DS-3SP	1.15	19.13	129	30.3	25
	1800	230	215T	D7C2K21	\$1,596	DS-3SP	1.15	19.87	105	35.5	25
10	3600	230	215T	D10C1K21	\$2,287	DS-3SP	1.15	20.63	92	40.0	25
	1800	230	215T	D10C2K21	\$1,794	DS-3SP	1.15	19.87	150	42.2	25

Note 23 Manual Reset Thermal Overload Protector
Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-Protected