

OEM Replacement for Specific Manufacturers

Catalog Number	Type	Dia.	HP	Volts	RPM	Speed	Amps	Rotation	Bearing	Enclosure	Cross Reference	Notes	Fig
----------------	------	------	----	-------	-----	-------	------	----------	---------	-----------	-----------------	-------	-----

LENNOX

Application: Direct Drive Blower

8052	PSC	5.6"	1/3	230	825	3	1.9	CCWLE	SAB	OAO	65G5901, KA55XJAK2549, 5KCP39NGM981AS		D2
LX7920	PSC	5.6"	1/2	115	1075	5	8	CCWLE	SAB	OAO	60L2201, K55HXHGB-8639, K55HXDUD-1245	43" Leads	D2
LX7921	PSC	5.6"	1/2	115	1075	5	8	CCWLE	SAB	OAO	60L2101, K55HXHFZ-8638, K55HXDUE-1249	43" Leads	D2
8064	PSC	5.6"	1/2	208-230	825	3	4.4	CCWLE	SAB	OAO	81G5101, K55HXJTT2904		C2
3275	PSC	5.6"	3/4	115	1075	4	10	CCWLE	BALL	OPEN	K55HXTMS9565, 28F0101	46" Leads	E2
8066	PSC	5.6"	3/4	208-230	1075	3	4.5	CCWLE	SAB	OAO	K55HTNW9654, 18J9601, 78F9201	Terminal Block Connector	E2
LX7924	PSC	5.6"	3/4	208-230	1075	5	4.6	CCWLE	SAB	OAO	13H3901, K55HXLCD-3607, K55HXDUD-1261		E2
LX7930	PSC	5.6"	3/4	460	1075	3	2.3	CCWLE	SAB	OAO	43G5201, K55HXEKA-7371, K55HXDUX-1258	36" Leads	E2

C2



D2



E2



† All marks shown within this document are properties of their respective owners.

