

Split Phase Hot Water Circulating Pump Open Drip-Proof (ODP)



APPLICATIONS:

Designed to meet manufacturer's requirements for use on hot water circulating pumps.

FEATURES:

- Painted Red To Indicate Hot-Water Usage
- 40°C Ambient
- Reversible Rotation
- Resilient Hub Rings
- Special Balance For Quiet Operation
- Class B Insulation
- 1725 RPM
- Automatic Reset Thermal Overload Protector
- Sleeve Bearings Have All Angle Thrust System
- Units Match OEM Performance And Mechanical Features
- Sleeve Bearings Unless Noted

Split Phase, NEMA Frame 48YZ

HP	Voltage	Catalog Number	Amps	Bolt Circle	Rings OC	SF	Rotation Shaft End	Ship Wt.	Notes	Industry Numbers
1/12	115	3255	2.5	4.63	5.94	1.75	CW	10		111034, 805316-010
1/6	115	3256	3.8	4.63	6.94	1.75	CW	13		111061, 817025-005
1/6	115	3257	3.8	5.00	6.94	1.75	CW	14		111036, 111031, 817025-001
1/4	115	3259	4.6	5.00	6.94	1.25	CW	15		111040, 817025-007, 111050
1/3	115	3260	6.0	5.86	6.94	1.30	CCW	15		169226, 816141-002, 169038

Capacitor Start, NEMA Frame 56YZ

HP	Voltage	Catalog Number	Amps	Bolt Circle	Rings OC	SF	Rotation Shaft End	Ship Wt.	Notes	Industry Numbers
1/2	115/208-230	3258	5.7/3.0-2.9	5.86	7.94	1.50	Rev	27	2	111044, 169228, 811757-001
3/4	115/208-230	3261	8.2/4.7-4.2	5.86	8.44	1.50	Rev	33	2	111047, 169230, 811757-002

Three Phase, Ball Bearing, C-Face, NEMA Frame 56CZ

HP	Voltage	Catalog Number	Amps	Bolt Circle	Rings OC	SF	Rotation Shaft End	Ship Wt.	Notes	Industry Numbers
1-1/2	208-230/460	3265	5.0-4.9/2.4	5.86	-	1.35	Rev	28	2, LA	169092, 169237, 816678-069

Note 2: Coupler assembly required for proper Bell & Gossett replacement

Note LA: Limited Availability

† All marks shown within this document are properties of their respective owners.

