

Permanent Split Capacitor Condenser Fan 5.0" Diameter, Totally Enclosed, Air Over (TEAO)



APPLICATIONS:

Residential condensing unit fan motor.

FEATURES:

- 42" Leads
- Shaft Down Mount
- #8-32 Studs
 - Fig A: 4.312" dia. bolt circle
 - Fig B: 4.464" dia. bolt circle
- Designed for use with 370V Capacitor
- 1/2" Dia. Shaft with Flat
- Reversible Rotation
- Automatic Reset Thermal Overload Protector




Figure A




Figure B

"Clam Shell" Single Speed, Stud Mount, Without Capacitor (Fig A)

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes	OEM
1/10	1075	208-230	2243	Ball	5.0	0.75	2.7	4.1	6.8	9		
1/8	1075	208-230	2249	Ball	5.0	0.90	2.7	4.1	6.8	10		
1/5	1075	208-230	2246	Ball	5.0	1.60	2.7	4.9	7.6	10		
1/4	1075	208-230	2250	Ball	7.5	1.70	2.7	4.9	7.6	11		

5.0" Single Speed, Stud Mount, Without Capacitor (Fig B) 4.464 BC

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes	OEM
1/20	1625	230	1989P	SAB	3.0	0.8	2.5	3.8	6.3	10	H35, H42, 98	CO
1/8	1550	230	1675	SAB	5.0	0.8	3.0	3.8	6.8	9	H35	TR
1/8-1/12	1075	208-230	5440H	Ball	5.0	0.8	3.0	5.0	8.0	10		
1/6	1075	208-230	1901	SAB	5.0	1.0	2.0	3.8	5.8	10		LE
1/4-1/6	1075	208-230	5441H	Ball	5.0	1.5	3.0	5.5	8.5	10		

BO = Bohn CO = Copeland LE = Lennox

Note 98: 50/60 Hz
 Note H35: Open Air Over
 Note H42: Shaft-down mounting

† All marks shown within this document are properties of their respective owners.

