

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® NEMA Premium®† Efficient – IE3



UTE

## APPLICATIONS:

For general industrial equipment including fans, blowers, compressors, pumps and direct connected equipment.

## FEATURES:

- World Motor® Features, Except Where Noted
- Class F Insulation, Class B Rise at Full Load On 60 Hertz Sine Wave Power
- Aluminum Frame (180-280), Rolled Steel (56-140)
- "CE" Mark on Nameplate (140 Frame & Larger)
- Shaft Slinger on Pulley End
- Full 50 & 60 Hertz Operating Data on Nameplate (03)
- Full HP @ 50 Hz
- 40°C Ambient, NEMA® Design B Performance On 60 Hertz Sine Wave Power
- Regreasable Shaft-End Bearings 180 Frame & Up
- Sealed Bearings 56-140 Frame, Double Shielded 180-280 Frame
- Suitable for Wye-Delta Start 250 Frame & Larger
- Dual Voltage Ratings Suitable for Part Winding Start (PWS) on Low Voltage
- Lifting Provisions 180 Frame & Up
- Conversion Kits: Drip Cover & Brakes (56-210 Frame), See Pages 263-266

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes	
1/4	1800	208-230/460	56	T14S2A	\$378	DS-3F	1.15	10.9	17	-	1.1-1.1/5	03, 19, NNP	
	1200	208-230/460	56	T14S3A	\$575	DS-3F	1.15	11.9	17	-	1.4-1.5/76	NNP	
1/3	1800	208-230/460	56	T13S2A	\$389	DS-3F	1.15	11.4	20	-	1.3-1.3/0.6	03, NNP	
1/2	3600	208-230/460	48	T12S1D4	\$432	DS-3F	1.00	10.7	19	-	1.8-1.8/1.0	03, NNP	
	3600	208-230/460	56	T12S1A	\$390	DS-3F	1.15	10.9	20	-	2.0-2.0/1.0	03, NNP	
	1800	208-230/460	56	T12S2A	\$482	DS-3F	1.15	11.9	21	-	1.8-1.8/0.9	03, NNP	
	1800	575	56	T12S2G	\$482	DS-3F	1.15	11.3	23	-	0.80	03, NNP	
	1200	208-230/460	56	T12S3A	\$552	DS-3F	1.15	11.9	23	-	2.2-2.3/1.1	NNP	
	1200	575	56	T12S3G	\$552	DS-3F	1.15	11.9	26	-	0.85	NNP	
3/4	3600	208-230/460	56	T34S1A	\$474	DS-3F	1.15	11.9	22	-	2.5-2.5/1.2	03, NNP	
	1800	208-230/460	56	T34S2A	\$518	DS-3F	1.15	11.9	23	-	3.0-3.0/1.5	03, NNP	
	1800	575	56	T34S2G	\$518	DS-3F	1.15	12.5	25	-	1.1	37, NNP	
	1200	208-230/460	143T	T34S3B14	\$713	DS-3F	1.15	12.8	30	75.5	3.4-3.5/1.7	NNP	
	1200	208-230/460	56H	T34S3AH	\$644	DS-3F	1.15	12.9	31	-	3.1-3.2/1.6	NNP	
1	3600	208-230/460	56	T1P1A	\$331	DS-3F	1.15	11.9	23	-	3.4-3.2/1.6	03, NNP	
	3600	208-230/460	56	U1E1D	\$415	DS-3F	1.25	12.5	32	-	3.1-2.7/1.4	03, NNP	
	3600	575	56	U1E1G	\$415	DS-3F	1.25	12.5	32	-	1.2	NNP	
	1800	208-230/460	56H	T1S2AH	\$504	DS-3F	1.15	12.4	30	-	3.3-3.2/1.5	NNP	
	1800	200	143T	U1P2H	\$654	DS-3XE	1.25	12.8	35	85.5	3.4		
	1800	208-230/460	143T	U1P2D	\$654	DS-3XE	1.25	12.8	76	85.5	3.1-3/1.5	03	
	1800	575	56H	T1S2GH	\$428	DS-3F	1.15	12.4	26	-	1.3	NNP	
	1800	575	143T	U1P2G	\$654	DS-3XE	1.25	12.8	40	85.5	1.1		
	1200	208-230/460	56H	T1S3A	\$725	DS-3F	1.15	13.4	32	-	3.7-3.8/1.9	03, NNP	
	1200	200	145T	U1P3H	\$789	DS-3XE	1.25	12.8	40	82.5	4.1		
	1200	208-230/460	145T	U1P3D	\$789	DS-3XE	1.25	12.8	40	82.5	3.6-3.5/1.8	03	
	1200	575	145T	U1P3G	\$789	DS-3XE	1.25	12.8	40	82.5	1.4		
	900	208-230/460	182T	U1E4D	\$1,260	DS-3FTE	1.25	12.8	60	74.0	4.4-4.7/2.4	03, NNP	
	1-1/2	3600	208-230/460	56H	T32S1AH	\$554	DS-3F	1.15	12.3	26	-	4.7-4.5/2.2	03, NNP
		3600	200	143T	U32P1H	\$768	DS-3XE	1.25	12.8	35	84.0	4.4	
3600		208-230/460	143T	U32P1D	\$768	DS-3XE	1.25	12.8	35	84.0	4.2-3.9/1.9	03	
3600		575	143T	U32P1G	\$768	DS-3XE	1.25	12.8	35	84.0	1.6		
1800		200	145T	U32P2H	\$679	DS-3XE	1.25	12.8	40	86.5	4.7		

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 37 Q-3 leads for across-the-line start  
Note NNP Non-NEMA Premium® Rating

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor

† All marks shown within this document are properties of their respective owners.



# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® NEMA Premium<sup>†</sup> Efficient – IE3

**NEMA  
Premium**



GENERAL PURPOSE UNIMOUNT  
GENERAL PURPOSE HOSTILE DUTY  
GENERAL PURPOSE CORRO-DUTY™  
GENERAL PURPOSE 841 PLUS™  
GENERAL PURPOSE e-LINE™  
GENERAL PURPOSE OPEN DRIPPROOF  
GENERAL PURPOSE HAZARDOUS LOCATION  
GENERAL PURPOSE AUTOMOTIVE DUTY  
COOLING TOWER DUTY  
HAZARDOUS LOCATION  
C-FACE MOTORS  
VARIABLE FREQUENCY

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1-1/2	1800	208-230/460	145T	U32P2D	\$679	DS-3XE	1.25	12.8	40	86.5	4.5-4.3/2.1	03
	1800	575	145T	U32P2G	\$679	DS-3XE	1.25	12.8	40	86.5	1.7	
	1800	208-230/460	56H	T32S2AH	\$481	DS-3F	1.15	12.9	34	-	5.1-5.2/2.6	NNP
	1200	208-230/460	56	T32S3AH	\$832	DS-3F	1.15	14.4	41	-	5.4-5.3/2.6	NNP
	1200	200	182T	U32P3H	\$842	DS-3XE	1.25	16.1	64	87.5	5.4	
	1200	208-230/460	182T	U32P3D	\$842	DS-3XE	1.25	16.1	60	87.5	4.8-4.7/2.3	03
	1200	575	182T	U32P3G	\$842	DS-3XE	1.25	16.1	60	87.5	1.8	
	1200	208-230/460	182T	S32P3A	\$842	DS-3XE	1.25	14.9	60	87.5	5.1-5.2/2.6	04,16,26,RS
2	900	208-230/460	184T	U32E4D	\$1,491	DS-3FTE	1.25	12.8	70	78.5	6.2-6.6/3.3	03, NNP
	3600	200	145T	U2P1H	\$842	DS-3XE	1.25	12.8	40	85.5	6.3	
	3600	208-230/460	145T	U2P1D	\$842	DS-3XE	1.25	12.8	40	85.5	5.4-4.9/2.5	03
	3600	575	145T	U2P1G	\$842	DS-3XE	1.25	12.8	40	85.5	2	
	3600	208-230/460	145T	T2P2AHZ	\$681	DS-3XE	1.25	12.8	40	85.5		
	3600	208-230/460	56H	T2S1AH	\$622	DS-3F	1.15	12.4	33	-	6.0-5.4/2.7	NNP
	3600	208-230/460	56HZ	T2E1AHZ	\$677	DS-3F	1.25	13.3	32	-	6.3-6.1/3.1	NNP
	3600	575	56H	T2S1G	\$622	DS-3F	1.15	12.4	31	-	2.3	NNP
	1800	208-230/460	56H	T2S2AH	\$520	DS-3F	1.15	12.9	36	-	7.2-7.1/3.4	NNP
	1800	208-230/460	56HZ	T2E2AHZ	\$544	DS-3F	1.25	13.8	36	-	6-5.9/3	NNP
	1800	200	145T	U2P2H	\$706	DS-3XE	1.25	12.8	45	86.5	6.2	
	1800	208-230/460	145T	U2P2D	\$706	DS-3XE	1.25	12.8	45	86.5	5.9-5.7/2.8	03
	1800	575	145T	U2P2G	\$706	DS-3XE	1.25	12.8	45	86.5	2.3	
	1200	200	184T	U2P3H	\$931	DS-3XE	1.25	16.9	74	88.5	7.2	
	1200	208-230/460	184T	U2P3D	\$931	DS-3XE	1.25	16.1	70	88.5	6.4-6.2/3.1	03
	1200	575	184T	U2P3G	\$931	DS-3XE	1.25	16.1	70	88.5	2.5	
	1200	208-230/460	184T	S2P3A	\$931	DS-3XE	1.15	15.9	70	88.5	6.4-6.2/3.1	04,16,26,RS
	900	200	213T	U2E4H	\$1,893	DS-3FTE	1.25	18.6	90	82.5	8.7	NNP
	900	208-230/460	213T	U2E4D	\$1,893	DS-3FTE	1.25	18.6	90	82.5	7.9-7.6/3.8	03, NNP
	900	575	213T	U2E4G	\$1,893	DS-3FTE	1.25	18.6	90	82.5	7.9-7.6/3.8	NNP
3	3600	200	145T	U3P1HF	\$933	DS-3XE	1.25	13.8	53	86.5	8.8	
	3600	200	182T	U3P1H	\$933	DS-3XE	1.25	16.1	60	86.5	8.8	
	3600	208-230/460	145T	U3P1DF	\$933	DS-3XE	1.25	13.8	73	88.5	-	03
	3600	208-230/460	182T	U3P1D	\$933	DS-3XE	1.25	16.1	60	88.5	8.4-7.8/3.9	03
	3600	575	145T	U3P1GF	\$933	DS-3XE	1.25	13.8	63	87.5	-	
	3600	575	182T	U3P1G	\$933	DS-3XE	1.25	16.1	60	87.5	3.1	
	3600	208-230/460	182T	S3P1A	\$933	DS-3XE	1.15	14.9	60	86.5	8.4-7.7/3.9	04,16,26,RS
	1800	208-230/460	182T	S3P2A	\$779	DS-3XE	1.15	14.9	60	89.5	8.4-7.8/3.9	04,16,26,RS
	1800	200	182T	U3P2H	\$779	DS-3XE	1.25	16.1	60	89.5	9.1	
	1800	208-230/460	182T	U3P2D	\$779	DS-3XE	1.25	60.0	89.5	89.5	8.4-7.8/3.9	03
	1800	575	182T	U3P2G	\$779	DS-3XE	1.25	16.1	60	89.5	3.2	
	1200	200	213T	U3P3H	\$1,430	DS-3XE	1.25	18.6	105	89.5	9.9	
	1200	208-230/460	213T	U3P3D	\$1,430	DS-3XE	1.25	18.6	110	89.5	9.3-8.6/4.3	03
	1200	575	213T	U3P3G	\$1,430	DS-3XE	1.25	18.6	110	89.5	3.4	
	1200	208-230/460	213T	S3P3A	\$1,430	DS-3XE	1.15	18.9	105	89.5	9.2-8.6/4.3	04,16,26,RS

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 04 On 60 Hertz Sine Wave power

† All marks shown within this document are properties of their respective owners.

Note 16 Motors marked 208-230/460 volts may not meet all NEMA (MG-1) performance standards when operated at 208 volts

Note 26 Does not include World Motor® features

Note NNP Non-NEMA Premium<sup>†</sup> Rating

Note RS Rolled Steel Frame



# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® NEMA Premium®† Efficient – IE3



UTE

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	“C” Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
3	900	200	215T	U3E4H	\$2,069	DS-3FTE	1.25	20.1	125	84.0	12.8	NNP
	900	208-230/460	215T	U3E4D	\$2,069	DS-3FTE	1.25	20.1	125	84.0	11.7-11.1/5.5	03, NNP
	900	575	215T	U3E4G	\$2,069	DS-3FTE	1.25	20.1	125	84.0	4.5	NNP
5	3600	200	184T	U5P1H	\$1,036	DS-3XE	1.25	16.9	70	89.5	14.0	
	3600	208-230/460	184T	U5P1D	\$1,036	DS-3XE	1.25	16.9	75	89.5	13.4-12.2/6.1	03
	3600	575	184T	U5P1G	\$1,036	DS-3XE	1.25	16.1	75	89.5	4.9	
	3600	208-230/460	184T	S5P1A	\$1,036	DS-3XE	1.15	15.9	70	88.5	13.6-12.1/6.1	04, 16, 26
	1800	208-230/460	184T	S5P2A	\$853	DS-3XE	1.15	15.9	70	89.5	13.5-12.5/6.2	04, 16, 26
	1800	200	184T	U5P2H	\$853	DS-3XE	1.25	16.9	70	89.5	14.1	
	1800	208-230/460	184T	U5P2D	\$853	DS-3XE	1.25	16.9	70	90.2	13.6-12.3/6.2	03
	1800	575	184T	U5P2G	\$853	DS-3XE	1.25	16.9	70	89.5	5.1	
	1200	208-230/460	215T	S5P3A	\$1,617	DS-3XE	1.15	18.7	120	89.5	5.0-14.1/7.0	04, 16, 26
	1200	200	215T	U5P3H	\$1,617	DS-3XE	1.25	20.1	135	89.5	15.9	
	1200	208-230/460	215T	U5P3D	\$1,617	DS-3XE	1.25	20.1	135	90.2	15-14/7	03
	1200	575	215T	U5P3G	\$1,617	DS-3XE	1.25	20.1	135	89.5	5.6	
	900	200	254T	U5E4H	\$2,558	DS-3FTE	1.25	23.9	180	85.5	17.3	NNP
	900	208-230/460	254T	U5E4D	\$2,558	DS-3FTE	1.25	23.9	180	85.5	16.4-15.4/7.7	03, NNP
	900	575	254T	U5E4G	\$2,558	DS-3FTE	1.25	23.9	180	86.5	6.1	NNP
7-1/2	3600	200	213T	U7P1H	\$1,555	DS-3XE	1.25	18.6	105	90.2	20.6	
	3600	208-230/460	213T	U7P1D	\$1,555	DS-3XE	1.25	18.6	100	91.7	19.7-17.9/8.9	03
	3600	575	213T	U7P1G	\$1,555	DS-3XE	1.25	18.6	100	89.5	7.5	
	3600	208-230/460	213T	S7P1A	\$1,555	DS-3XE	1.15	18.9	105	89.5	19.9-17.9/9.0	04, 16, 26
	3600	208-230/460	213T	U7P1AF	\$1,555	DS-3XE	1.25	16.9	70	89.5	19.5-17.1/8.9	
	1800	208-230/460	213T	S7P2A	\$1,233	DS-3XE	1.15	18.9	105	91.7	20.0-18.1/9.1	04, 16, 26
	1800	200	213T	U7P2H	\$1,233	DS-3XE	1.25	18.6	105	91.7	20.8	
	1800	208-230/460	213T	U7P2D	\$1,233	DS-3XE	1.25	18.6	110	91.7	20-18.2/9.1	03
	1800	575	213T	U7P2G	\$1,233	DS-3XE	1.25	18.6	110	91.7	7.2	
	1200	200	254T	U7P3H	\$2,570	DS-3XE	1.25	23.9	180	91.0	21.8	
	1200	208-230/460	254T	U7P3D	\$2,570	DS-3XE	1.25	23.9	200	91.7	20.2/10.1	03
	1200	575	254T	U7P3G	\$2,570	DS-3XE	1.25	23.9	200	91.0	8.3	
	900	200	256T	U7E4H	\$3,449	DS-3FTE	1.25	25.6	300	86.5	25.4	NNP
	900	208-230/460	256T	U7E4D	\$3,499	DS-3FTE	1.25	25.6	300	86.5	23.8-22.2/11.1	03, NNP
	900	575	256T	U7E4G	\$3,449	DS-3FTE	1.25	25.6	300	86.5	8.8	NNP
10	3600	200	215T	U10P1H	\$1,575	DS-3XE	1.25	20.1	120	90.2	27	
	3600	208-230/460	215T	U10P1D	\$1,575	DS-3XE	1.25	20.1	125	91.7	26.4-23.5/11.8	03
	3600	575	215T	U10P1G	\$1,575	DS-3XE	1.25	20.1	125	91.7	9.4	
	3600	208-230/460	215T	S10P1A	\$1,575	DS-3XE	1.15	18.9	120	90.2	26.5-23.5/11.7	04, 16, 26
	1800	208-230/460	215T	S10P2A	\$1,392	DS-3XE	1.15	18.9	120	91.7	26.5-23.9/11.9	04, 16, 26
	1800	200	215T	U10P2H	\$1,392	DS-3XE	1.25	20.1	135	91.7	27.5	
	1800	208-230/460	215T	U10P2D	\$1,392	DS-3XE	1.25	20.1	133	91.7	26.5-23.9/12	03
	1800	575	215T	U10P2G	\$1,392	DS-3XE	1.25	20.1	135	91.7	9.6	
	1200	200	256T	U10P3H	\$2,936	DS-3XE	1.25	25.6	210	91.7	28.2	
	1200	208-230/460	256T	U10P3D	\$2,936	DS-3XE	1.25	25.6	250	91.7	25/12.5	03
	1200	575	256T	U10P3G	\$2,936	DS-3XE	1.25	25.6	210	91.7	9.8	

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate  
 Note 04 On 60 Hertz Sine Wave power

Note 16 Motors marked 208-230/460 volts may not meet all NEMA (MG-1) performance standards when operated at 208 volts  
 Note 26 Does not include World Motor® features  
 Note NNP Non-NEMA Premium® Rating  
 † All marks shown within this document are properties of their respective owners.



# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® NEMA Premium<sup>†</sup> Efficient – IE3

**NEMA  
Premium**



GENERAL PURPOSE UNIMOUNT  
GENERAL PURPOSE HOSTILE DUTY  
GENERAL PURPOSE CORRO-DUTY™  
GENERAL PURPOSE 841 PLUS™  
GENERAL PURPOSE e-LINE™  
GENERAL PURPOSE OPEN DRIPPROOF  
GENERAL PURPOSE HAZARDOUS LOCATION  
GENERAL PURPOSE AUTOMOTIVE DUTY  
COOLING TOWER DUTY  
HAZARDOUS LOCATION  
C-FACE MOTORS  
VARIABLE FREQUENCY

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
15	3600	200	254T	U15P1H	\$2,541	DS-3XE	1.25	23.9	190	91.0	40	
	3600	208-230/460	215T	U15P1AF	\$2,541	DS-3XE	1.25	21.6	140	91.0	39-35/17.7	
	3600	208-230/460	254T	U15P1D	\$2,541	DS-3XE	1.25	23.6	185	91.0	39-35/17.7	03
	3600	575	254T	U15P1G	\$2,541	DS-3XE	1.25	23.6	185	91.0	14.1	
	1800	200	254T	U15P2H	\$2,039	DS-3XE	1.25	23.9	190	92.4	42	
	1800	208-230/460	254T	U15P2D	\$2,039	DS-3XE	1.25	23.6	240	92.4	40-37/18.4	03
	1800	575	254T	U15P2G	\$2,039	DS-3XE	1.25	23.6	240	92.4	14.6	
20	3600	200	256T	U20P1H	\$2,791	DS-3XE	1.25	25.6	210	91.7	53	
	3600	208-230/460	256T	U20P1D	\$2,791	DS-3XE	1.25	25.6	220	91.7	51-46/22.9	03
	3600	575	256T	U20P1G	\$2,791	DS-3XE	1.25	25.6	220	91.7	18.3	
	1800	200	256T	U20P2H	\$2,472	DS-3XE	1.25	25.6	230	93.0	54	
	1800	208-230/460	256T	U20P2D	\$2,472	DS-3XE	1.25	25.6	250	93.0	53-47/23.7	03
	1800	575	256T	U20P2G	\$2,472	DS-3XE	1.25	25.6	250	93.0	19	
25	3600	208-230/460	284T	U25P1D	\$3,612	DS-3XE	1.25	28.3	280	91.7	56.8/28.4	
	3600	208-230/460	284TS	U25P1DS	\$3,612	DS-3XE	1.25	26.9	280	91.7	56.8/28.4	
	3600	575	284T	U25P1G	\$3,612	DS-3XE	1.25	28.3	280	91.7	22.7	
	3600	575	284TS	U25P1GS	\$3,612	DS-3XE	1.25	26.9	280	91.7	22.7	
	3600	200	284T	U25P1H	\$3,612	DS-3XE	1.25	28.3	280	91.7	65.0	
	3600	200	284TS	U25P1HS	\$3,612	DS-3XE	1.25	26.9	280	91.7	65.0	
	1800	208-230/460	284T	U25P2D	\$3,003	DS-3XE	1.25	28.3	280	93.6	58.6/29.3	
	1800	208-230/460	284TS	U25P2DS	\$3,003	DS-3XE	1.25	26.9	280	93.6	58.6/29.3	
	1800	575	284T	U25P2G	\$3,003	DS-3XE	1.25	28.3	280	93.6	23.4	
	1800	575	284TS	U25P2GS	\$3,003	DS-3XE	1.25	26.9	280	93.6	23.4	
	1800	200	284T	U25P2H	\$3,003	DS-3XE	1.25	28.3	280	93.6	67.0	
	1800	200	284TS	U25P2HS	\$3,003	DS-3XE	1.25	26.9	280	93.6	67.0	
	30	1800	208-230/460	286T	U30P2D	\$3,547	DS-3XE	1.25	28.3	300	93.6	70.0/35.0
1800		208-230/460	286TS	U30P2DS	\$3,547	DS-3XE	1.25	26.9	300	93.6	70.0/35.0	
1800		575	286T	U30P2G	\$3,547	DS-3XE	1.25	28.3	300	93.6	28.1	
1800		575	286TS	U30P2GS	\$3,547	DS-3XE	1.25	26.9	300	93.6	28.1	
1800		200	286T	U30P2H	\$3,547	DS-3XE	1.25	28.3	300	93.6	81.0	
1800		200	286TS	U30P2HS	\$3,547	DS-3XE	1.25	26.9	300	93.6	81.0	

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

† All marks shown within this document are properties of their respective owners.

