

Control Power Transformer, 750va, PRI 240x480v, SEC 120x240v, Domestic,



Figure similar

| | |
|-------------------------|---------------------------|
| Product brand name | Control Power Transformer |
| Product designation | MT |
| Special product feature | Robust design |

General technical data

| | |
|---|-----------------------|
| Weight [lb] | 28.1 lb |
| Height x Width x Depth [in] | 5.39 × 5.25 × 7.65 in |
| Ambient temperature [°F] during operation | -4 ... +104 °F |
| Ambient temperature during operation | -20 ... +40 °C |
| Country of origin | Mexico |
| Operating apparent output rated value | 750 V·A |

Enclosure

| | |
|-----------------------|------|
| Design of the housing | Open |
|-----------------------|------|

Mounting/wiring

| | |
|--|----------------------------------|
| Mounting position | Any |
| Mounting type | Surface mounting |
| Type of electrical connection at output for main current circuit | Screw-type terminals (touchsafe) |

| | |
|---|----------------------------------|
| Type of electrical connection at input for main current circuit | Screw-type terminals (touchsafe) |
|---|----------------------------------|

Inputs/ Outputs

| | |
|--|--------------|
| Input dimensions of primary voltage | 240x480vac |
| Output dimensions of secondary voltage | 120x240vac |
| Phase number of the inputs | 1 |
| Electrical input frequency | 50 ... 60 Hz |
| Input voltage _1 | 240 V |
| Input voltage _2 | 480 V |
| Phase number of the outputs | 1 |
| Electrical output frequency | 60 ... 50 Hz |
| Output voltage _1 rated value | 120 V |
| Output voltage _2 rated value | 240 V |

Certificates/approvals

| | |
|----------------------------|----------|
| Certificate of suitability | UL / CSA |
|----------------------------|----------|

Further information

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/US/en/ps/US2:MT0750M>

last modified: 08/07/2017