

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :						
Product line : Rolled Steel Single-Phase		Product code : 15099741				
		Catalog # : 00318OS1C184T-S				
Frame : 182/4T Output : 3 HP (2.2 kW) Poles : 4 Frequency : 60 Hz Rated voltage : 208-230 V Rated current : 13.7-12.8 A L. R. Amperes : 95.9-89.6 A LRC : 7.0x(Code H) No load current : 4.91-5.70 A Rated speed : 1765 rpm Slip : 1.94 % Rated torque : 8.93 ft.lb Locked rotor torque : 275 % Breakdown torque : 245 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.2781 sq.ft.lb Design : L		Locked rotor time : 10s (cold) 6s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Cooling method : IC01 - ODP Mounting : F-1 Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ³ : 67.3 lb				
Output	25%	50%	75%	100%		
Efficiency (%)	71.3	73.0	80.0	81.5		
Power Factor	0.51	0.82	0.88	0.92		
Foundation loads						
Max. traction : 106 lb						
Max. compression : 173 lb						
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6206 ZZ		6205 ZZ		
Sealing	:	Without Bearing Seal		Without Bearing Seal		
Lubrication interval	:	-		-		
Lubricant amount	:	-		-		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	09/03/2021				1 / 1	